· Enquiries regarding translation rights should be addressed to Amalgamated Wireless Valve Company Pty., Ltd., 47 York Street, Sydney, Australia.

# RADIOTRON DESIGNER'S HANDBOOK

# Edited By F. LANGFORD-SMITH

B.Sc., B.E. (1st class honours)
Senior Member I.R.E. (U.S.A.)
A.M.I.E. (Aust.)

#### FOURTH EDITION

Published by the Wireless Ptess
for

AMALGAMATED WIRELESS VALVE COMPANY PTY. LTD.
47 YORK STREET, SYDNEY, AUSTRALIA
1953

Reproduced and Distributed
by
Tube Division
RADIO CORPORATION OF AMERICA
HARRISON, N. J.

First Edition 1934

Second Edition 1935

Third Edition 1940

Fourth Edition 1952

COPYRIGHT. ALL RIGHTS RESERVED

1956

This book or any part thereof must not be reproduced in any form without the written permission of Amalgamated Wireless Valve Company Pty., Ltd.

Set up and printed in Australia by Simmons Ltd., 31-33 Parramatta Road, Glebe.

Wholly reproduced in U.S.A. by lithographic process

under direction of

Commercial Engineering Tube Division RADIO CORPORATION OF AMERICA Harrison, New Jersey 

August, 1956

# PREFACE

This book has been written as a comprehensive, self-explanatory reference handbook for the benefit of all who have an interest in the design and application of radio receivers or audio amplifiers. Everything outside this field—television, radio transmission, radar, industrial electronics, test equipment and so on-has been excluded to limit the book to a reasonable size.

An effort has been made to produce a handbook which, in its own sphere, is as selfcontained as possible. Extensive references to other sources of information have been included for the reader who might require additional detail.

The success of the previous edition, of which over 280,000 copies have been sold throughout the world, encouraged Amalgamated Wireless Valve Company Pty. Ltd., to undertake the compilation of the present up-to-date edition which is more complete, great pains having been taken to fill in many of the gaps in the data published This has involved a considerable amount of both experimental and analytical work by the editor and by engineers assisting in the project. Some original work, previously unpublished, has been included.

Although the various chapters have been written by individual authors, all are truly the result of team work, each having been carefully and critically examined by several other engineers specializing in that particular field. In this way the accuracy of mathematical calculations and of individual statements was checked and re-checked to ensure that the reader would not be misinformed.

I wish to express my grateful thanks to Mr. R. Lambie, Manager, Mr. D. M. Sutherland, Works Manager, and to the following collaborating engineers—

J. E. Bailey, Dr. W. G. Baker, D. Barnett, J. D. G. Barrett, Dr. G. Builder, N. V. C. Cansick, W. N. Christiansen, Dr. E. R. Dalziel, K. G. Dean, H. L. Downing, J. Gilchrist, I. C. Hansen, R. Herbert, F. Holloway, I. Hood, D. G. Lindsay, W. S. McGuire, E. J. Packer, J. Pritchard, R. J. Rawlings, B. Sandel, J. Stacey, R. D. Stewart, J. E. Telfer, R. Vine, E. Watkinson.

I also wish to express my thanks to Mr. R. Ainsworth for his invaluable work in sub-editing and assistance in indexing and to Mr. R. H. Aston for compiling data.

#### F. Langford-Smith

Amalgamated Wireless Valve Company Pty. Ltd.

#### NOTES

References to valve types are to the prototype (e.g. 6J7) and include all equivalent types (e.g. 6]7-G, 6]7-GT etc.) unless otherwise indicated.

If any errors are noted, please write to the Editor, Radiotron Designer's Handbook, Amalgamated Wireless Valve Co. Pty. Ltd., 47 York Street, Sydney, Australia.

#### **ACKNOWLEDGEMENTS**

The editor wishes to acknowledge his indebtedness to the publishers of the following periodicals for permission to reproduce the diagrams listed below. In some cases the diagrams are based largely on the originals, although modified.

#### PERIODICALS

Audio Engineering 13. 50D, 50E. 14. 1A, B, C, D, E, F, G, H. 15. 15, 16, 57A, 57B, 60. 16. 15. 17. 7, 8, 15A, 15B, 15C, 18, 19A, 19B, 19C, 20, 22, 24B, 24C, 27A, 27B, 27C, 31, 37A. 19. 6A. 20. 10, 13, 14.

A.W.A. Technical Review 25. 33, 34, 35, 36, 37, 38, 39. 26. 6. 27. 44.

Communications 7. 72, 73. 16. 16. 18. 17, 18. 23. 17, 18, 19, 20, 21, 22, 23, 24, 25, 26.

Electronic Engineering 5. 13E, 13F, 13G, 13H, 13J, 13K, 13L, 13M, 13N, 13P, 13Q, 13R, 13S, 13T, 13U, Table 5. 7. 51D. 11. 7, 8, 9, 10, 11, 12, 13. 12. 3B, 3C, 11A, 11B. 15. 4, 63. 17. 21, 26. 18. 6A, 6B.

Electronic Industries 17. 6.

Electronics 1. 8. 4. 34. 5. 21, 22. 7. 51. 9. 17, 18. 12. 47A, 47B, 48. 15. 17, 18A, 18B, 38, 39, 45, 46, 52, 53, 61. 16. 4, 10, 12, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28. 21. 9. 35. 24, 25. 36. 3, 5.

FM-TV Radio Communication 17. 35. 20. 25, 26, 27.

Journal Acoustical Society of America 20. 28.

Journal British I.R.E. 5. 13C, 13D.

Proceedings I.R.E. (U.S.A.) 7. 58, 59. 12. 7C. 13. 9B. 14. 6. 20. 24. 25. 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21. 30. 4, 5, 6, 7, 8, 9. 37. 2, 3, 4.

Proceedings I.E.E. 7. 60, 65, 69, 70.

Proceedings I.R.E. Australia 35. 19, 20, 21.

Q.S.T. 16. 13.

Radio 13. 50D, 50E. 15. 47A, 47B.

Radio and Hobbies (Australia) 15. 14B, 35B, 37B, 37C.

Radio and TV News 15. 43A, 43B. 16. 14. 18. 7A, 7B.

Radio Craft 15. 42, 44A, 49, 54. 17. 33.

Radio Electronics 15. 64.

R.C.A. Review 17. 37A. 27. 20, 21, 25, 27.

Tele-Tech 15. 14A. 36. 2. 38. Chart 38.4.

T.V. Engineering 10. 10.

Wireless Engineer 5. 13B. 7. 75, 76, 77, 78, 79, 80, 81, 82, 83. 11. 1, 6A.

Wireless World 4. 10, 26. 7. 51A, 54B, 54C, 55D, 55E, 55F, 59C. 12. 34, 35, 39. 15. 5, 13, 41, 50, 51, 55, 56A, 56B, 58A. 16. 8, 9, 11. 17. 24A, 28, 32, 35B, 35C, 35D, 35E, 35F, 35G. 18. 26. 20. 5, 9, 11, 12, 16, 17. 31. 6.

Reference numbers are given either in the titles or in the text. Lists of references giving authors' names and details of articles are given at the end of each chapter.

#### ACKNOWLEDGEMENTS (Continued)

#### BOOKS AND OTHER PUBLICATIONS

The editor desires to acknowledge his indebtedness to the authors and publishers of the following books and publications for permission to reproduce the diagrams and tables listed below.

Redrawn by permission from ELECTRONIC TRANSFORMERS AND CIRCUITS by R. Lee, published by John Wiley & Sons, Inc., 1947. Fig. 5.23.

Redrawn by permission from General Electric Company from TRANSFORMER ENGINEERING—1st ed. by Blume, Camilli, Boyajian & Montsinger, published by John Wiley & Sons, Inc. 1938. Fig. 5.18B.

Redrawn by permission from ELEMENTS OF ACOUSTICAL ENGINEERING (2nd ed.) by H. F. Olson, copyrighted by D. Van Nostrand Company Inc. Table 19.7. Fig. 20.30.

Redrawn by permission from NETWORK ANALYSIS AND FEEDBACK AM-PLIFIER DESIGN by H. W. Bode, Bell Telephone Laboratories Inc., copyrighted 1945 by D. Van Nostrand Company Inc. Figs. 7.55A, 7.55B, 7.55C, 7.56A.

Other acknowledgements are given in the titles.

#### OTHER PUBLICATIONS

Aerovox Research Worker, Vol. 11, Nos. 1 and 2, January-February 1939, Figs. 5 and 6. Published by permission of Aerovox Corporation. Tables 38. 43, 44. Charts 38. 1, 2.

Allegheny Ludlum Steel Corporation—curves 3.6% silicon steel. Fig. 5. 20. American Standards Association "American Standard for Noise Measurement" Z24.22-1942. Figs. 19. 7, 8.

Australian Radio Technical Services and Patents Co. Pty. Ltd.—Technical Bulletins. Figs. 15. 22, 23, 24, 25, 26, 27, 43, 31. 3, 4, 5.

Amalgamated Wireless Australasia Ltd. Figs. 18. 7. 28. 2.

Electrical and Musical Industries. Fig. 17. 25.

Jensen Manufacturing Company—Jensen Technical Monograph No. 3. Figs. 14. 2, 3, 4, 5.

P. R. Mallory & Co. Inc. "Fundamental Principles of Vibrator Power Supply" Figs. 32. 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13.

National Bureau of Standards Circular C74, Fig. 208 redrawn and published by permission of National Bureau of Standards. Fig. 10. 3.

Standard Transformer Corporation "Engineering a transformer." Figs. 5. 18C, 18D. Table 38. 70.

General Electric Company Ltd. "Radio receiver for use with high fidelity amplifiers." Fig. 15. 62A.

Radio and Television Manufacturers Association (U.S.A.)—Extracts from, or summaries of, the following Standards:

ET-107, ET-109, ET-110, REC-11, REC-101, REC-103, REC-104, REC-105, REC-106-A, REC-107, REC-108, REC-113, REC-114, REC-115-A, REC-116, REC-117, REC-118, REC-119, REC-121, REC-128, S-410, S-416, S-417, S-418, S-504, SE-101-A, SE-103, SE-105, TR-105-A, TR-113-A.

Note:—References in the text to R.M.A. Standards should be taken as having been issued by RTMA.

I.R.E. Standards, Figs. 3. 11B, 15. 37. 1, 2, 3, 4.

Radio Industry Council—Information from standards on resistors and capacitors. Chapter 38 Sections 2 and 3.

Radio Corporation of America. 1. 6. 2. 32A, 33, 34, 35, 47. 3. 16, 17. 10. 6. 13. 26, 30, 48. 17. 5A. 23. 9, 10, 11, 12, 13, 14, 15, 16. 30. 2A, 2B, 2C, 11. 33. 14. 35. 17.

# CHAPTER HEADINGS

	PART 1: THE RAD	OIO VA	LVE				
Сна	PTER						PAGI
1	INTRODUCTION TO THE RADIO VALVE	•••	•••	•••	•••	•••	. 1
	Valve Characteristics	•••				•••	13
3	THE TESTING OF OXIDE-COATED CATHODE H	ligh-va	CUUM	RECEIV	ING VA	LVES	68
	PART 2: GENERAL THEORY	AND	СОМ	PONE	NTS		
4	THEORY OF NETWORKS						128
5	TRANSFORMERS AND IRON-CORED INDUCTOR	ZS.		• • •			199
6	MATHEMATICS			***			254
7	NEGATIVE FEEDBACK			•••			306
8	WAVE MOTION AND THE THEORY OF MOD	ULATIO	N	•••	•••	•••	403
9	TUNED CIRCUITS					•••	407
10	CALCULATION OF INDUCTANCE			•••			429
11	DESIGN OF RADIO FREQUENCY INDUCTORS			•••	•••	•••	450
	PART 3: AUDIO FR	EQUE	NCIES	S			
12	AUDIO FREQUENCY VOLTAGE AMPLIFIERS	711 CH				2000	481
13	in an apresentation and per a Commercial and access the commercial and approximate and approximate and a second and approximate and a second and a s						544
14	FIDELITY AND DISTORTION					12223	603
15	TONE COMPENSATION AND TONE CONTROL				48378;	52524	635
16	Volume Expansion, Compression and L						679
17	REPRODUCTION FROM RECORDS	IMILITIAC	• • • • •				701
18	MICROPHONES, PRE-AMPLIFIERS, ATTENUATO	DC ANTO		 D¢		110 - 1	775
19	Units for the Measurement of Gain a			ш	\$3.55%		806
20	_	ND NO	ISE	•••	* * *	•••	831
21	THE NETWORK BETWEEN THE POWER OUTPU	T STAG	E AND	THE I	OUDSPE	AKED	
21	THE NEIWORK BETWEEN THE TOWER COTT	)I DING	E MIL	1110 2	OODSI L		000
	PART 4: RADIO FR	EOUE	CIES	3			
22	CARDAGARATAR PER IN MARKANITANAN BARANTANAN BARANTANAN BARANTANAN						890
22	Aerials and Transmission Lines	***	•••	• • •	404040	•••	912
23	RADIO FREQUENCY AMPLIFIERS	•••	•••	• • •	• • •	•••	947
24	OSCILLATORS		***	•••	• • •	•••	962
25	FREQUENCY CONVERSION AND TRACKING		****	***	***		1020
26	INTERMEDIATE FREQUENCY AMPLIFIERS	***	***	* * *	*.*.*		
27	DETECTION AND AUTOMATIC VOLUME CON		***	•••	***		1072
	REFLEX AMPLIFIERS						
29	LIMITERS AND AUTOMATIC FREQUENCY CO	NTROL	•••	***	• • •	•••	114/
PA	RT 5: RECTIFICATION, REGULAT	TION,	FILT	ERIN	G AN	D H	UM
30	RECTIFICATION						1161
31	FILTERING AND HUM	•••				•••	1192
32	VIBRATOR POWER SUPPLIES	• • •			***		1202
	C W B			***			
	PART 6: COMPLETE R	ECEIV	ERS				
34	Types of A-M Receivers					70 <b>40404</b>	1223
	DESIGN OF SUPERHETERODYNE A-M RECEI		100000				1228
	DESIGN OF F-M RECEIVERS						1287
37	RECEIVER AND AMPLIFIER TESTS AND MEA						1297
	PART 7: SUNDR	Y DAT	ГΑ				
38	TABLES, CHARTS AND SUNDRY DATA				• •		1328
	See next page for detailed	List o	of Cor	itents.			
	SUPPLEME			***		6,000	1475
	COLLEGIA						

# PART 1: THE RADIO VALVE

# CHAPTER 1. INTRODUCTION TO THE RADIO VALVE

SECTI	ION									PAGE
1.		Y AND EMISSI	on			•••				1
2.	Тне Сомр	ONENT PARTS	OF RADIO	VALVE	is.					4
	(i)	Filaments, ca								4
	(ii)	Grids	***		***		•••	• • •	• • •	5
	(iii)	Plates	***					35.5.5	***	5
	(iv)	Bulbs						***	***	5
	(v)	Voltages wit	h valve o <sub>l</sub>	peration	١		***	•••	• • •	5
3.	Types of	RADIO VALVES	· · · ·					(#1#1#		6
0.000	(i)	Diodes							•••	6
	(ii)	Triodes	3 29000	***			1.****	•••		7
	(iii)	Tetrodes		***					,	7
	(iv)	Pentodes	X		•••		* * * 5	•••	* * *	7
	(v)	Pentode pov	- <del> </del>	iers			•••	• • •	* * *	8
	(vi)	Combined v	alves	•••			• • •	• • • •		8
	(vii)	Pentagrid co	nverters		•••				***	8
4.	MAXIMUM	RATINGS AND	TOLERAN	CES						9
	(i)	Maximum r			interpr	etation		•••	•••	9
	(ii)	Tolerances								9
5.		AND HEATER	VOLTAGE/	CURREN	т Сна	RACTER	ISTICS			10
6.		MBERING SYST		#0#6#?	****			XXXX		10
7.	REFERENCE						•••	***	***	12
2		CHAPTER		VE C	HARA	CTE	RIST	ICS		13
1.	TOTAL CALCULATION OF STATES	EFFICIENTS		•••	•••	•••		***	***	
2.	CHARACTE	RISTIC CURVES		M. 1808	****	• • •	• • •	***	•••	15
	(i)	Plate charac			•••	•••	•••	••••	•••	15
	(ii)	Mutual cha			• • •	•••	•••	• • •		17
	(iii)	Grid currer		3117.132	• • •	•••	•••	•••	•••	18
	(iv)	Suppressor			255	•••	• • •	5 <b>5</b> ,55	7.1.	21
	(v)	Constant cu		ves	**************************************	•••	•••	F	***	22 23
	(vi)	"G" curve	S	 d		* *	•:•:±::	); <b>*/*</b> (*)	***	23
	(vii)	Drift of ch	aracteristic	as wari	ig inc	#00/#Q	• • •	***	* * *	24
	(viii)	Effect of he		Re Autr	atton	***		•••	* * *	
3.	RESISTANC	e-Loaded Am	<b>IPLIFIERS</b>	•••	***	***		•••		24
	(i)	Triodes		• • •	• • •	•••	• • •	•••		24
	(ii)	Pentodes .		•••		•••	•••	•••	•••	26
4.	TRANSFOR	MER-COUPLED	AMPLIFIE	RS			•••	•••		27
8888	(i)	With resist	ive load	•••	***			55.63	***	27
	(ii)	Effect of p	27		( <b>*</b> ) <b>*</b> ( *	•••	•••	***		28
	(iii)	With i-f vo				***	•••	***	• • •	28
	(iv)	R-F amplif	fiers with	sliding	screen	***	***	***		28

SECT	ION								PAGE
	(v)	Cathode loadlines	***		• • •	***	•••	52.20	29
-	(vi)	With reactive loads	***			***	#0 <b>*</b> 0#0	*.5.*	30
5.		PERATION OF PENTODE	920	( <b>*</b> (*(*))		• • •	***		34
	(1)	Triode operation of			1	• • •	*(***)	(***)	34
	(ii)	Examples of transco			ilation	•••	5 xxx	14441	34
	(iii)	Triode amplification		• • •	•••	•••	202020		35
	(iv)	Plate resistance	•••		•••	•••			36
	(v)	Connection of suppr	되는 집 이렇게 좀하는 것이다					•••	36
6.		N FACTORS, AND THE	JALCULA?	TION OF	CHAR	ACTERI:	STICS O	THER	20
		SE PUBLISHED		···	***	•••	• • •	S	36
	(i)	The basis of valve of				***	• • •	•••	36
	(ii)	The use of valve co				•••			37
	(iii)	The calculation of va	aive char	acterist	ics otn	er than	tnose	pub-	40
	/: N	lished				•••			40
~	(iv)	The effect of change	하면 남자를 잃었다면 뭐라면 그 그리다면요?			ions		•••	42
7.		IVALENT CIRCUITS AN			•••	• • •	• • •	•••	45
	(1)	Constant voltage equ			•••		250	***	45
	(ii)	Constant current eq	uivaient	circuit	•••	***	•		46
0	(iii)	Valve vectors		***	***	***	• • •	***	47
8.		AITTANCES		 	2014	• • •			49
	(1)	Grid input impedan			nce	• • •	• • •		49
	(ii)	Admittance coefficier					•••	•••	50
	(iii)	The components of					resistan	ce—	
	24	input capacitanc							51
	(iv)	Typical values of sh		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					55
	(v)	Change of short-circ	uit-input	capaci	tance v	vith tr	anscond	luct-	
		ance	909(A)			***	***	***	55
	(vi)	Grid-cathode capacit							56
	(vii)	Input capacitances of		les (pu	blished	value	s)	•••	56
	(viii)	Grid-plate capacitan	ce		• • •	• • •	• • •	•••	57
9.	MATHEMAT	ICAL RELATIONSHIPS	• • •	• • •	• • •			•••	57
	(i)	General	***	15.50	***	***	* * *	3.50.50.5.	57
	(ii)	Resistance load	S	140.50	***	***	• • •	(****)	58
	(iii)	Power and efficiency							59
	(iv)	Series expansion; re			***		£3040		61
	( <b>v</b> )	Series expansion; go							63
	(vi)	The equivalent plate			n		•••	•••	63
	(vii)	Dynamic load line—			• • •				64
	(viii)	Valve networks—gen			•••	***	S		64
	(ix)	Valve coefficients as				• • •	5.***	5 <b>91908</b>	64
	( <b>x</b> )	Valve characteristics	at low p	plate ci	urrents				65
10.	REFERENCES	*** *** ***		30.00			•••	• • •	66
CH	APTER 3	. THE TESTIN	G OF	OVII	DF-C	) A TE	D C	АТНО	DE
CIL	MILK 3							AIIIO	DE
\$ <b>4</b> 00 5	D	HIGH-VACUUN	I KECI	SIVIN	G V	TLAE	3		<b>60</b>
1.		ESTING PRACTICE			***	***	***	***	68
	(i)	Fundamental physica			* * *	***		***	69
	(ii)	Basic functional char							70
	(iii)	Fundamental charact				•••		• • •	73
	(iv)	Valve ratings and th		ing eff	ect on	operat	ion	•••	75
		(A) Limiting ra				•••	• • •	•••	75
		(B) Characterist		lly rate	d	3.5.5	***	***	75
		(C) Rating syste		:	***	*(***)	+/(*0*/)	***	77
		(D) Interpretation			ı ratin	gs	•••	***	77
	(37.18	(E) Operating of			***		(40.00)		80
	(v)	Recommended pract		operation	on			19.00	80
		(a) Mounting	0.81818.0		•••	• • •	#1.000001 •1.0000€1	• • •	80
		(b) Ventilation	***	10.00	•••	• • •			81

SECT	ION	/ N TT				PAGE
		(c) Heater-cathode insulation	•••	•••	•••	81
		(d) Control grid circuit resistance	•••	•••	••	82 84
		(e) Operation at low screen voltages	•••	•••	•••	84
		(f) Microphony	***	***		84
		(g) Hum	•••	<b>K</b> ( <b>X</b> ) <b>X</b> ( <b>X</b> )		84
		(h) Stand-by operation	•••	• • •	***	04
2.	CONTROL	OF CHARACTERISTICS DURING MANUFACTURE			(0.00000)	85
	(i)	Importance of control over characteristics		*		85
	(ii)	Basic manufacturing test specification				85
	(iii)	Systematic testing				86
	(iv)	Tolerances on characteristics				88
						90
3.		of Testing Characteristics	• • •	***	•••	89
	(i)	General conventions	•••	***	•••	90
	(ii)	General characteristics	•••	•••		91
		(a) Physical dimensions	•••	•••	•••	91
		(b) Shorts and continuity	•••	•••	•••	91
		(c) Heater (or filament) current	•••	\$***x		93
		(d) Heater to cathode leakage	•••	***	•••	94
		(e) Inter-electrode insulation		•••	• • •	94
		(f) Emission		***		94
	22 - 12 - 12	(g) Direct inter-electrode capacitances	•••	***	• • •	95
	(iii)	Specific diode characteristics	•••		•••	99
		(a) Rectification test	•••		• • •	99
		(b) Sputter and arcing	•••	•••	•••	100
		(c) Back emission	•••	* * *	••••	100
		(d) Zero signal or standing diode curr			•••	101
	(iv)	Specific triode, pentode and beam tetrode		racteristic	cs	101
		(A) Reverse grid current		***		101
		(B) Grid current commencement volt	(SP0)	(#389E	***	102
		(C) Positive grid current			• • •	102
		(D) Positive voltage electrode current		•••	•••	103
		(E) Transconductance or mutual con-	ducta	nce	•••	103
		(F) Amplification factor	•••	***	•••	104
		(G) Plate resistance	•••	***	•••	104
		(H) A.C. amplification	•••		• • •	105
		(I) Power output	•••	***		105
		(J) Distortion	•••	• • •	•••	106
		(K) Microphony	•••		•••	107
		(L) Audio frequency noise	•••	•••	•••	107
		(M) Radio frequency noise	•••	•••	•••	107
		(N) Blocking	•••	• • •	•••	107
		(O) Stage gain testing	•••	59.8.8	***	108
		(P) Electrode dissipation		0290909	•••	108
	(v)	Specific converter characteristics	•••		•••	108
		(A) Methods of operation including	oscilla	itor exci	tation	
		(1) Oscillator self-excited		***		108
		(2) Oscillator driven	• • •	• • • •	•••	109
		(3) Static operation	•••	•••	•••	109
		(B) Specific characteristics	•••	•••	•••	109
		(a) Reverse signal grid curre		• • • • •	•••	109
		(b) Signal-grid current conin			•••	109
		(c) Mixer positive voltage el			nts	109
		(d) Mixer conversion transco	nduct	ance	•••	109
		(e) Mixer plate resistance		***	* * *	111
		(f) Mixer transconductance	• • •	SEE # 2	• • •	111
		(g) Oscillator grid current	•••			111

SECT	TION		X 12 X					PAGE
			lator plate cu			• • •		113
			lator transcor			***	•••	113
		21 Table 1 Tab	lator amplific	12:			***	113
			lator plate re		•••			113
		(l) Signa	ıl-grid blocki	ng	• • •			113
		(m) Micr	ophony	***		•••		113
		(n) R-F	noise		***			113
	(vi)	Tests for special chara	acteristics			0.000		113
		(A) Short-circuit	input admitt	ance			•••	113
		(B) Short-circuit	feedback adr	mittance				117
		(C) Short-circuit	output admi-	ttance		***		117
		(D) Short-circuit	forward adm	ittance				117
		(E) Perveance	***					117
	(vii)	Characteristics by puls	se methods—	point b		nt		118
	(viii)	Characteristics by cur		2000			•••	119
1		E TESTING				14		120
4.		726-1700 1700 1700 1700 1700 1700 1700 1700	•••	***	***	***	#(#) #()	120
	(i)	Relevant characteristic			•••		• • •	
	(11)	Valve specifications			• • •	V. W. &	****	120
	(iii)	Testing procedure	•••	•••	•••		• • •	120
5.	SERVICE TE	STING AND SERVICE TE	STER PRACTIC	CE				121
	(i)	Purpose and scope of	service testin	ng and	discu	ission of	as-	
		sociated problems						121
	(ii)	Fundamental character	ristics which	should	be te	ested		122
	(iii)	Types of commercial	testers	200.00				122
	(iv)	Methods of testing cha	The state of the s	comme	rcial s	ervice te	sters	123
	<b>\-&gt;</b>	(a) Shorts testing		(****)		***		123
		(b) Continuity tes		14.44		***		123
		(c) Heater to cath	170 UN N	•••		***		123
		(d) Emission testing	(10 <del>00</del> 00)			• • •		123
		(e) Mutual condu	(Table )					123
		(f) Plate conducta	그래마 (1) [1] 2 [2] [2] . 그림 생각 [2] [2] [2] [2]			* * *	•••	124
					• • •	•••	• • •	124
		(g) Reverse grid	The second secon	ıg		205	<b>*</b> (*)**	
		(h) Power output		(1.75	***	****	# * * * * * * * * * * * * * * * * * * *	124
		(i) Conversion co		•		(#3 <b>*</b> 3*	•••	124
		(j) Oscillator mu		ance tes	ung	***	***	124
		(k) Noise testing		* * *		****	• • •	124
		(l) A.C. amplifica			***			124
	(v)	A.C. versus d.c. elect	rode voltages	in test	ers	•••	• • •	124
	(vi)	Pre-heating	•••		•••			125
	(vii)	Testing procedure		•••		•••	***	125
6.	REFERENCES							125
	DADT	2. CENEDAL TI	IEODV AN	ID CO	MDC	MENT	CC	
	PARI	2: GENERAL TH	IEURI AN	ND CO	MP	JNEN	1.3	
		CHAPTER 4. TH	EORY OF	NETW	OR	KS		
				- 1 1				
1	CURRENT A	ND VOLTAGE						128
- 1	(i)	n: .		1.5.5		•••	* * *	128
	(ii)	Alternating current	***	98880	3.5	2.27	***	
	1,000,000,000,000		and current	 Horr	(*).****	***	• • • •	129
2	(iii)	Indications of polarity	and current	now	• • •	***	•••	130
2.	RESISTANCE		**** *****	***		* * *		130
	(i)	Ohm's Law for d.c.	XXX XXX	(54.414)		• • •	• • •	130
	(ii)	Ohm's Law for a.c.	***					131
	(iii)	Resistances in series	***		•••		•••	131
	(iv)	Resistances in parallel			•••		• • •	132
	( <b>v</b> )	Conductance in resist	ive circuits				0.0	133

SECT	ION							PAGE
3.	Power			24%	7.245.0	1.00		133
	(i)	Power in d.c. circuits				-		133
	(ii)	Power in resistive a.c. ci						133
	<b>/</b> /			The same of the sa	\$3655W	250505		
4.	CAPACITANO	CE			(10000)			134
	(i)	Introduction to capacitan	ice				0=00=0=0	134
	(ii)	Condensers in parallel as						135
	(iii)	Calculation of capacitance			• • •	•••		135
	(iv)	Condensers in d.c. circu		•••		***		136
	86 SAS			• • •	• • •	28083	•••	137
	(v)	Condensers in a.c. circui	its	•••		***		151
_	T	_						140
Э.	INDUCTANC			•••	• • •		***	140
	(i)	Introduction to inductan						140
	(ii)	Inductances in d.c. circu		•••				141
	(iii)	Inductances in series and	d parallel			• • •		141
	(iv)	Mutual inductance	••					142
	(v)	Inductances in a.c. circu	its					142
	(vi)	Power in inductive circu		9:5050			1903.00	143
	V.5.52			*:*:*	•••	•••	(845-F)	
6.	IMPEDANCE	AND ADMITTANCE			1			144
0.		Impedance, a complex of		***	*(*3*0)		****	144
	(i)			•••	***		***	BARRE.
	(ii)	Series circuits with L, C			***	***		144
	(iii)	Parallel combinations of	1,000					147
	(iv)	Series-parallel combination	1.53			1999		149
	(v)	Conductance, susceptance				•••		153
	(vi)	Conversion from series t	to parallel	impeda	nce			157
7.	<b>Networks</b>	ANN 45.0 KM						158
	(i)	Introduction to networks			-			158
	(ii)	Kirchhoff's Laws .		·	4	S114555	0.000	160
	(iii)	Determined dissidence						161
	(iv)	Therranin's Theorem			***	3.50	17.67.19.	164
	\$1.00°	Norton's Theorem	50.50 (5.50.5)	***	• • •		***	165
	(v)		Th	•••		***		
	(vi)	Maximum Power Transf		:m	•••	• • •	•••	165
	(vii)	Reciprocity Theorem		***	•••		• • •	165
	(viii)	Superposition Theorem.		•••	4000	•••	• • •	165
	(ix)	Compensation Theorem.				• • •		166
	(x)	Four-terminal networks					***	166
	(xi)	Multi-mesh networks						167
	(xii)	Non-linear components i	in network	and the same and t		•••	***	170
	(xiii)	Phase shift networks						170
	(xiv)	Transients in networks		***	*, *(*)			171
	M 536	References to networks			***			
	(xv)	References to hetworks		•••	• • •	•••	•••	171
0	T							100
8.	FILTERS	- 200 - 120		***	•••	•••	• • •	172
	(i)			***		•••	• • •	172
	(ii)	Resistance-capacitance fil	100	700		-pass		172
	(iii)	Special types of resistance	ce-capacita	ance filt	ers		***	176
	(iv)	Iterative impedances of	four term	inal net	works		***	176
	(v)	Image impedances and i	mage tran	sfer cor	istant (			4411766
	. N. 20 Z	• • • • • • • • • • • • • • • • • • •			• • •			177
	(vi)					3.5.5.5		179
	(vii)	"C la " Eleana		•••	* * *	7.0 m (m)	• • •	179
				***	***		• • •	
	(viii)		101 101 101 101 101 101 101 101 101 101	***	909080	**************************************	• • •	182
	(ix)			• • •	• • •	•••	• • •	184
	( <b>x</b> )	Frequency dividing netw	orks	***	***			184
	(xi)	References to filters .	2024 A2000	X6X5X5X				184

SECT									PAGE
9.	PRACTICAL	Resistors, Condensers	AND IN	IDUCTO	RS	•••	•••	•••	186
	(i)	Practical resistors		•••	• • •	• • •	•••	•••	186
	(ii)	Practical condensers	•••		***		•••		191
	(iii)	Combination units	•••	***	***	•••		***	197
	(iv)	Practical inductors	***	* *2	***			***	197
	( <b>v</b> )	References to practical	resisto	rs and	conden	sers		***	198
СН	APTER 5.	TRANSFORMERS	S ANI	IRO	N-CO	RED	IND	UCT	ÖRS
1.	IDEAL TRAI	NSFORMERS		1964					199
÷7650	(i)	Definitions				0.00			199
	(ii)	Impedance calculations	-single	e load					200
	(iii)	Impedance calculations	THE RESERVE TO SERVE THE PROPERTY OF SERVE THE						201
	(>								
2.	PRACTICAL	Transformers	•••						204
	(i)	General considerations	E					14.4	204
	(ii)	Effects of losses		ESSAILS :		•••			205
	( <del>-</del> )	21 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -		1,400,000					
3.	Audio-Fre	QUENCY TRANSFORMERS	73 <b>*</b> 73 <b>*</b> 13*17		•••				206
	(i)	General considerations		OKOKOK			• • •		206
	(ii)	Core materials		***	***				207
	(iii)	Frequency response an	d distor	rtion					
	(/	(a) Interstage trans							209
		(b) Low level tran	5.5 <b>2</b>						210
		(c) Output transfo							211
	(iv)	Designing for low leak							217
	(v)	Winding capacitance				5/5/17 5/5/5/	((\$205) 5 <b>4:4:</b> 40	***	219
	(vi)	Tests on output transf		32,455					227
	(vii)	Specifications for a-f to	10023	mers	***	*(***	- 1.70 ES	18885	228
	(11)	Specifications for a r t	ansion	incro	•••	•••	(4.4.42	***	220
4	MAGNETIC	CIRCUIT THEORY	2000		***	***	4:4(4)		229
•	(i)	Fundamental magnetic					•••	***	229
	(ii)	The magnetic circuit							231
	(iii)	Magnetic units and co		_					232
	(111)	Magnetic units and co	1110101	ii iucio	-0			••••	
5.	Power Tr.	ANSFORMERS			74744				233
ATTENIA.	(i)	General		065600	5884				233
	(ii)	Core material and size		( • • • )		•••			234
	(iii)	Primary and secondary					•••		235
	(iv)	Currents in windings	• • • • •		• • •				236
	(v)	Temperature rise		A	•••				236
	(vi)	Typical design	***						237
	(vii)	Specifications for power			S				241
	·>								
6.	IRON-CORE	D INDUCTORS							242
57	(i)	General		2000	14/4/9	***	£ (* 0.4)		242
	(ii)	Calculations—general	1228				4 + 4		242
	(iii)	Effective permeability			444		***		243
	(iv)	Design with no d.c. fl							243
	(v)	Design of high Q indu			18-620				245
	(vi)	Design with d.c. flux					0555 5755		247
	(vii)	Design by Hanna's me		• • • •		***	• • •	•••	248
	(viii)	Design of inductors fo				nario (finite)	#1#1#1		249
	N (50%)	Measurements		1.74			2502025		250
	(ix) (x)	Iron-cored inductors in					202020 202020		251
	(A)	and the second in the second in				ज्या <del>वि</del> र	e. e. 90.0	as to the file of	10000000000000000000000000000000000000
7	REFERENCES	· · · · · · · · · · · · · · · · · · ·	•••	•••	•••	•••	•••		252

SECT	ION									PAGE
		CHA	PTER 6.	MAT	HEM	ATIC	S			
1	ARITHMETIC	AND THE	SLIDE RULE							255
•	(i)	Ti			•••	•••				255
	(ii)	Powers and			•••	. • . • . •	••••			255
	(iii)	Logarithms	•••		*.*.*			***	•	255
	(iv)	The slide r		•••				• • •	•••	257
	(v)	Short cuts		ic		•••	•••	• • •	•••	258
2	201000								viewe.	259
2.	ALGEBRA		• •••		•••		•••	***		260
	(i)	Subtraction	***	•••	•••	•••	•••	•••		260
	(ii) (iii)	Multiplicati		•••	• • •	•••	•••			260
	550.25	D: :::		*.*.*	***	•••	•••			260
	(iv)	Domes		* * *	•••	•••	10.20			260
	(v) (vi)	Doots		•••	• • • •		***			261
	(vii)	Brackets an	d simple m	aninula	tione	•••	•••			261
	(viii)	Factoring	3000	0 <del>,7</del> 0.			•••	***		262
		Proportion	V • • (• )	•••	* * * * *	an la		***		262
	(ix)	Variation	•••	•••	•••	•••				262
	(x) (xi)	Inequalities	• • •	•••		•••				262
	(xii)	Functions		***	•••	•••				263
	(xiii)	Equations	2.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1	***	* * *	***				263
	(xiv)	Formulae a	nd laws		•••	•••		•••		265
	(xv)	Continuity					•••		•••	265
	(xvi)	Progression							****	266
	(xvi)		c and expor				···	•••		267
	(xviii)	Infinite seri	[1] . [2] 보이보고 보다 - 보이라면 10 10 10 10 10 10 10 10 10 10 10 10 10					•••	•••	268
	(xix)	Hyperbolic	**************************************		•••					269
	(xx)		proximation							271
		per	100	×		(628)	57070	12,61		272
3.				3.53	***	•••	*(***)	•••	• • •	272
	(i)	Plane figur		 -£1:	٠٠٠	***	#.#.#X	A	***	275
	(ii)		nd volumes			***	•••			275
	(iii)	1 rigonome	trical relatio	nsnips	***	•••	***	•••	***	000000000
4.	PERIODIC I	HENOMENA.		•••		•••				278
5	GRADUICAL	REPRESENTA	ATION AND	NOTA	TION					279
٦.						10.00	E		NAME:	279
	(i) (ii)		e equation			-11-11	1		***	281
	(iii)	Three vari				i i				281
	(iv)		d j notation	0020000		V 9	٧			282
-										285
6.	9.43	ALGEBRA ANI	DE MOIV	RES II	HEUKEM	l		•••	•••	285
	(i)	Complex a	lgebra with	regula	r coord	amates	•••	•••	•••	286
	(ii)		lgebra with		Coordii	lates	•••		•••	287
	(iii)	De Moivre	's Theorem	8 150	•••	•••	•••	*.*.*:	***	201
7.	DIFFERENT	IAL AND INT	EGRAL CALO	CULUS	•••		•••			289
	(i)		rate of char		•••					289
	(ii)	Differentia			•••			•••		291
	(iii)	Integration		•••	•••		• • •			294
	(iv)	Taylor's S	eries	•••	•••			***		298
	(v)	Maclaurin's		***	•••	***	***	•••	•••	299
0		ERIES AND F	TARMONICS	912-23		***		904040		299
8.		Periodic w	aves and th	e Four						299
	· (ii)		lications of							302
	(iii)		Harmonic A							302
	(111)	Grapincar								
Q	REFERENCE	2			400000		5.000	3.00		304

(xvi)

2 ECT	ION				PAGE
		CHAPTER 7. NEGATIVE FEEDBA	ACK		
848	Emman				306
0.00		T-11-1		•••	306
	(i) (ii)	Negative voltage feedback at the mid-freque		•••	307
	(iii)	Negative voltage feedback at the mid-freque			312
	(iv)	Bridge negative feedback at the mid-frequen		•••	313
	(v)	Combined positive and negative at the mid-	2000 I TO	•••	314
	(vi)	Comparison between different fundamental ty			J. 1
	(*1)	frequency			315
2	PRACTICAL				316
۷.	(i)	TD1 1 C 11			316
	(ii)	The cathode degenerative amplifier and pha			327
	(iii)	Voltage feedback from secondary of output			330
	(iv)	Voltage feedback from plate—transformer in			332
	(v)	TT 1 C 11 1 C 1			332
	(vi)	TT 1. C. distribution for a second			334
	(vii)	77 1. C 31. L			344
	(viii)	Cathode coupled phase inverters and amplifi			347
	(ix)	Line			348
	(x)	Some special features of feedback amplifiers		***	352
	(xi)	O 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	•• •••	•••	352
	(xii)	Chales assumed whose investor	** ***		355
3.	STABILITY,				356
	(i)	0. 1 11	1919 97979		356
	(ii)	O 10.1 C . 1.10.		•••	356
	(îii)	Relationship between phase shift and attenu			359
	(iv)	Design of 1 and 2 stage amplifiers		••••	364
	(v)	Design of multistage amplifiers	**	•••	365
	(vi)	Tiffe of feedback on feedback recommend			378
	(vii)	Design of amplifiers with flat frequency res	ponse		379
	(viii)	Constancy of characteristics with feedback .	5		388
	(ix)	TOTAL OF C. Alberta and alberta alaife			389
4.	SPECIAL A				389
5.	VALVE CHA	RACTERISTICS AND FEEDBACK	***		390
	(i)	Triode cathode follower			390
	(ii)	Pentode cathode follower			393
	(iii)	Triode with voltage feedback			394
	(iv)	Pentode with voltage feedback, transformer	coupled		395
	(v)	Cathode degenerative triode			397
	(vi)	Cathode degenerative pentode			399
	(vii)	Cathode-coupled triodes		***	399
	(viii)	Feedback over two stages		***	399
6.	REFERENCES	то Feedback			399
7.	OVERLOADIN	IG OF FEEDBACK AMPLIFIERS ON TRANSIENTS.			1477
	OTTABET	D O WATE MORION AND THE	m		
	CHAPTE	ER 8. WAVE MOTION AND THE	THEORY	OF	
		MODULATION			
1.	INTRODUCT	ION TO ELECTROMAGNETIC WAVES			403
70.E	(i)	Wave motion	•••	***	403
	(ii)	Electromagnetic spectrum		•••	404
	(iii)	Wave propagation			404
2.	(10mm-2) 0.0 0.0	ON OF INTELLICENCE			405
	(i)	Introduction			405
	(ii)	Dadia talagraphy			405
	(iii)	Dadie Adambana		•••	405
3.	REFERENCES				400

CON		TTC
	100 000 000	

SECTI	CONTENTS					PAGE
JECII	CHAPTER 9. TUNED CIR	CUIT	ΓS			86.752.8
1.	INTRODUCTION	•••				407
60.00		•••	•••			408
3.					•••	409
						410
5.	GENERAL CASE OF SERIES RESONANCE					412
107214753 10724	SELECTIVITY AND GAIN					412
6.	(i) Single tuned circuit	•••	***	•••	• • •	412
		***	***	•••	•••	413
	(iii) Coupled circuits—tuned primary, tur	ned sec	ondary	· • • •	•••	414
	(IV) Coupled design	•••	•••		***	415 416
	(') Co-Pion	• • •		• • •	936050	
7.	SELECTIVITY—GRAPHICAL METHODS		• • •	35.4.5	***	416 416
	(i) Single tuned circuit		N# #2#	189690	•••	417
	(ii) Two identical coupled tuned circuits	· · · ·	1.6.454	•••	****	418
8.	COUPLING OF CIRCUITS	***	S • • • ·		•••	418
	(i) Mutual inductive coupling (ii) Miscellaneous methods of coupling			***		418
	(ii) Miscellaneous methods of coupling (iii) Complex coupling					420
	RESPONSE OF IDENTICAL AMPLIFIER STAGES IN C					421
	Universal Selectivity Curves		•••	3 <b>434.4</b>		421
SE581						423
11.	SUMMARY OF FORMULAE FOR TUNED CIRCUITS	• • •	****	5.00 M		427
12.	References	•••	E ATTENT	•••		12.
	CHAPTER 10. CALCULATION OF	FINE	UCT	ANCI	3	
1	SINGLE LAYER COILS OR SOLENOIDS					429
	(i) Current-sheet inductance					429
	(ii) Solenoids wound with spaced round	wires	•••			430
	(iii) Approximate formulae	•••	•••	•••	•••	432
	(iv) Design of single layer solenoid	 n T a	nd I	* * *	***	433 435
	(v) Magnitude of the differences between (vi) Curves for the determination of the	" curre	nt-shee	t" ind	uc-	133
	(vi) Curves for the determination of the					437
	(vii) Effect of concentric, non-magnetic s					438
2	MULTILAYER SOLENOIDS					441
2.	(i) Formula for current sheet inductant	ce				441
	(ii) Correction for insulation thickness		101E2			442
	(iii) Approximate formulae	• • •		• • •		442
	(iv) Design of multilayer coils	•••	• • •	•••	•••	443 444
	(v) Effect of a concentric screen	\$18.50	***	•••	•••	445
3.	TOROIDAL COILS	 th sing	 la lave	 r mind	 ina	445
	(i) Toroidal coil of circular section with (ii) Toroidal coil of rectangular section	with sir	nole lav	er win	dino	
	The section of rectangular section	with r	nultilay	er win	ding	445
	Manager and the second					445
4.	FLAT SPIRALS	***		***		445
	(i) Accurate formulae (ii) Approximate formulae	26.65	***	***	•••	446
5	MUTUAL INDUCTANCE	•••	***		•••	446
).	(i) Accurate methods	30.00		***	•••	446
	(ii) Approximate methods	3690		***	***	
6	LIST OF SYMBOLS	18188	• • • •	***	•••	
7	REFERENCES	•••	•••	•••		448

SECT	ION		63TH (752.7							PAGE
CH	APTER 11.	<b>DESIGN</b>	OF R	RADIO	FRE	QUEN	1CY	INDU	JCTO	ORS
1.	INTRODUCTION	v	• • •	• • •	18040	•••			00000000	450
2.	SELF-CAPACIT	ANCE OF COIL	s					•••		451
	(i) <b>E</b>	effects of self-o	capacita	nce		***			•••	451
	(ii) C	Calculation of	self-cap	acitance	of sir	igle-laye	r sole	enoids		451
	(iii) N	Aeasurement o	f self-ca	apacitan	ce	•••	•••	•••	•••	453
3.	Intermediati	E-FREQUENCY \	WINDIN	GS		• • •		•••		453
	(i) A	Air-cored coils	***	* * *	•••	3.* 3*. <b>*</b>	•••			453
	* 1 P	ron-cored coils		•••		•••	***	***	•••	454
	2000 A	expanding sele					•••		*(*)*)	455
	8 5	Calculation of	5000000		univei	rsal coil	S	•••		456
	A 160	Miscellaneous of	3.50	rations		***	•••	***	•••	458
4.		VE-BAND COIL	S	***		•••	***	****		459
	310.52	Air-cored coils		•••	•••		•••	•••	•••	459
		ron-cored coil		• • •	•••	• • •	•••		•••	460 461
	1997 TOWN 200	Permeability tu Matching		***	#1.51 <b>2</b> 0	0.445	****	3*5*8#	***	462
	and the Supplemental Control of the		****	***	#C***	\$1564G	1168/052		181818	
5.			• • •	***	•••	***	***	• • •		463
	\ /	Design Miscellaneous	 fanturas	***	***	***	•••		•••	463 468
4600			icatures		***	\$12°\$1	•••	•••	***	
6.	- International control of the property of the control of the	JENCY CHOKES		***	• • •	• • •	•••	1.		474
	Control of the contro	Pie-wound cho	Kes	•••	•••	•••		•••	• • •	474
	705	Other types	(****)	14.015	•••	35.50	110,5%		31.57	475
7.	1200			2000	• • •	•••		S * 3 * 3 * 3	•••	476
		General consid	eration	S	•••	***	*(*(*)	***	•••	476
	1000	Baking	#(#)#:		***	•••	• • •			476 477
	500 S 500 S 500 S	Impregnation Flash dipping								477
		Materials								477
0	(*1 <b>N</b> 95 <b>46</b> ) 5									478
8.	REFERENCES	***	• • •	•••	•••	• • •	•••	•••	•••	410
		PART 3	: AUI	DIO F	REOU	JENCI	ES			
77062700										
CI	HAPTER 1	2. AUDIO	FRE	QUEN	CY V	VOLTA	AGE	AMP	LIF	ERS
1.	INTRODUCTIO	ON		•••	•••					48
		Voltage amplif	iers	• • •	•••		•••		•••	48
2.	RESISTANCE-	CAPACITANCE (	COUPLE	D TRIOR	ES	(4.4.4)		•••		482
		Choice of ope		- AECO. 120					•••	482
		Coupling cond	lenser	***		* * *)		***	***	483
	` '	Cathode bias	***						***	484
		Fixed bias		747472		272727	•••	•••	•••	48'
	` '	Grid leak bias			***	• • •	•••	•••	•••	489
	10 to 1 to	Plate voltage			 nid fra		•••	•••	• • •	489
		Gain and dist Dynamic char			mu-ire			• • •	• • •	49 49
	(ix)	Maximum vol			d dist	ortion	1,515557	•••	10.558	49
	(x)	Conversion fa					•••	•••		49
	(xi)	Input impeda					***			49
	(xii)	Equivalent cir								49
	(xiii)	Voltage gain	1.75				<b>6</b> 830		•••	49
	(xiv)	Comments o		ulated	charac	cteristics	of	resista	ance-	
		coupled to	riodes			• • •	•••	•••	•••	49

495

ION				
	E-CAPACITANCE COUPLED PENTODES	7.5.5.E	1.11	•••
(i)	Choice of operating conditions	0.000 PG	S1100	1.55
(ii)	Coupling condenser	***	***	***
(iii)	Screen by-pass		•••	
(iv)	Cathode bias			
(v)	Fixed bias	•••		
(vi)	Dynamic characteristics of pentodes	•••		
(vii)	Gain at the mid-frequency			****
(viii)	Dynamic characteristics of pentodes and	d comp	arison	with
× ×	triodes			
(ix)	Maximum voltage output and distortion	***		
(x)	Conversion factors with r.c.c. pentodes			3.00
(xi)	Equivalent circuit of r.c.c. pentode			2.0.00
(xii)	Voltage gain and phase shift			
(xiii)	Screen loadlines		9999	
Service Control of the Control of th	Combined screen and cathode loadlines and		ect of	23
(xiv)		u me en	cct or	
, ,	ances			
(xv)	Remote cut-off pentodes as r.c.c. amplif		•••	• • •
(xvi)	Multigrid valves as r.c.c. amplifiers	***	•••	•••
(xvii	어느 보이를 보고 그 바이를 보고 있는 것이 없는 것이다.	· · · · · ·		
(xvii		ics of	resist	ance-
	coupled pentodes	•••		• • •
TRANSFOR	RMER-COUPLED VOLTAGE AMPLIFIERS			***
(i)	Introduction			
(ii)	Gain at the mid-frequency			
(iii)	Gain at low frequencies			
(iv)	Desirable valve characteristics			
(v)	Equivalent circuits			909000
WW. 250	Gain and phase shift at all frequencies		****	(200000)
(vi)	그 그렇게 하는데 그리고 그렇게 되었다. 그 그리고 그렇게 되었다. 그리고 그렇게 되었다.			
(vii)	Transformer characteristics	DITES.		3.53
(viii)	20	14 14.	•••	00.00
(ix)	Valve loadlines	• • •		• • •
( <b>x</b> )	Maximum peak output voltage	•••		
(xi)	Transformer loading	•••		
(xii)	Parallel feed	• • •	• • •	• • •
(xiii	Auto-transformer coupling	T :	5.5.5	
(xiv)	Applications	***	*:*:*:	
(xv)	Special applications			
CHOKE-C	COUPLED AMPLIFIERS		***	
(i)	Performance	***	***	
(ii)	Application	mall.		1243
METHOD				
707	Methods involving iron-cored inductors			
(i)				
(ii)	Phase splitter	•••	•••	•••
(iii)	Phase inverter	***	***	* * *
(iv)	Self-balancing phase inverter		***	<b>5</b> 05.05
(v)	Self-balancing paraphase inverter		•••	
(vi)	Common cathode impedance self-balance			***
(vii)	Balanced output amplifiers with highly	accurat	e bala	nce
(viii	33 - 1898 B. T. W. 1888 M. T. C. W. 1888 M. M. B.		***	
Push-Pu				
(i)	Introduction	1200		
(ii)	Cathode resistors			
	The state of the s			
(iii)	Push-pull impedance-coupled amplifiers			171.0.00
(iv)		manic		
(4 <b>3</b> 45.23 <b>4</b> 50	ment	***	353735	1686
(v)	Phase compressor	5 <b>5.5</b> (5)	1979.9	***

SECT	ION								PAGE
8.	IN-PHASE A	MPLIFIERS				•••	•••		529
	(i)	Cathode-coupled amp	lifiers				•••	•••	529
	(ii)	Grounded-grid ampli	fiers				•••	•••	529
	· (iii)	Inverted input ampli	fiers						529
	(iv)	Other forms of in-ph	nase amp	lifier	s	•••			529
•	Depres Con	A							<b>E00</b>
9.		UPLED AMPLIFIERS	·	• • •		•••	•••	• • •	529
	(i)	Elementary d-c ampl	iners	***	8 <b>*2*</b> *8	2000	#25U#	***	529
	(ii)	Bridge circuit	***	***	<b>2.0000</b> 00			* • •	530
	(iii)	Cathode-coupled	***	•••	•••	***	***	•••	531
	(iv)	Cathode follower		***	• • •	• • •	***	•••	531 532
	(v)	Phase inverter	•••	• • •		•••	•••	•••	532
	(vi)	Screen coupled Gas tube coupled	•••		• • •	•••	•••	•••	532
	(vii) (viii)	Modulation systems	•••	•••	***	•••	•••	***	532
	(ix)	Compensated d.c. an		•••	•••	• • •	•••	•••	533
	(x)	Bridge-balanced direct		it am	nlifiere	***	2000	***	533
	(xi)	Cascode amplifiers		it aii	ipmicis			***	533
	(AI)	Cascouc ampimers	***	•••		•••	•••	• • •	,,,,
10.	STABILITY,	DECOUPLING AND HU	м	•••	***		54046	1414	535
	(i)	Effect of common in	npedance	in p	power su	ipply	100		535
	(ii)	Plate supply by-passi	ng				•••		535
	(iii)	Plate circuit decoupli	ng			•••			535
	(iv)	Screen circuit decoup	oling		***				537
	(v)	Grid circuit decoupli	ng	•••	***	•••	14.40		538
	(vi)	Hum in voltage amp	lifiers	•••	***			•••	538
11	Тъ	D A							E 40
11.	4.24	AND PULSES IN AUDI	IO FREQI	JENCY	AMPLI	FIERS		•••	540
	(i)	Transient distortion	***	•••	• • •	•••	7 <b>*</b> • •	•••	540
	(ii)	Rectangular pulses	•••	•••	•••		•••	•••	<b>54</b> 0
12.	MULTISTAG	E VOLTAGE AMPLIFIER	s						541
	(i)	Single-channel ampli	73 ATAMAN	•••	***		07.54T 0#.≠0#		541
	(ii)	Multi-channel amplif		•••	***	•••	***		541
669420				1305030	8050	1.00,00,00	(3/2)		
13.	REFERENCES		***		•••				542
(	HAPTER	13. AUDIO FR	EOLIE	MOV.	DOW	ED A	MOTI	CICI	00
8	SIMI IEK	15. AUDIO FR	EQUE	NCI	row	EK A	MILTI	.FIEF	(3
1	INTRODUCT	ION							EAA
	2001 (1.000 km) - v. 100 (100 km) - v. 100 km		 omnlifica		***	• • •		•••	544
	(i) (ii)	Types of a-f power Class of operation	ampimei		•••	•••			544
	(iii)	그렇게 그 그 아이들이 아이들이 아이들이 아이들이 아이들이 아이들이 아이들이	 af ma		 _1:6			• • •	545
	(iv)	Some characteristics				(/ <b></b>	•••	•••	545
	(14)	Effect of power supp	ory on p	ower	ampune	ers	•••	•••	547
2.	CLASS A S	INGLE TRIODES				50404040	10 <b>4</b> . <b>4</b> 0 <b>4</b> 0 1		548
	(i)	Simplified graphical				tout a	nd dist		
	(ii)	General graphical car							550
	(iii)	Optimum operating of					***		555
	(iv)	Loudspeaker load			•••				558
	(v)	Plate circuit efficienc							559
	(vi)	Power sensitivity	, p	121219	Pw				559
	(vii)	Choke-coupled ampli	fier						559
	(viii)	Effect of a.c. filamer							560
	(ix)	Overloading			•••			•••	560
	(x)	Regulation and by-p							560
				VI 134 C.	ALTERNATIVE CHECKING TO	A COMPANY AND A STATE OF THE PARTY AND A STATE	100 F 100 F 2	0.500	C. C. C. C. C.

SECT	ION			PAGE
3.	CLASS A M	ULTI-GRID VALVES	***	560
	(i)	Introduction		560
	(ii)	Ideal pentodes	• • •	561
	(iii)	Practical pentodes—operating conditions		*561
	(iv)	Graphical analysis—power output and distortion	on	563
	(v)	Rectification effects	***	565
	(vi)	Cathode bias	***	565
	(vii)	Resistance and inductance of transformer prim	arv	566
	(viii)	Loudspeaker load		566
	(ix)	Effects of plate and screen regulation		568
	(x)	D	***	569
	(xi)	Common Marian and Alexander		569
	(xii)	Partial triode ("ultra-linear") operation of pe		570
4		TION A ALERT TETERO		570
		T O A AD	•••	571
Э.		1. [2018년 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	***	571
	(i)	Introduction		573
	(ii)	Theory of push-pull amplification	***	577
	(iii)	Power output and distortion	***	579
	(iv)	Average plate current	*****	500
	(v)	Matching and the effects of mismatching	•••	500
	(vi)	Cathode bias	10.00	500
	(vii)	Parasitics	- A AD	583
6	(10)24242	PENTODES AND BEAM POWER AMPLIFIERS, CLASS	$A, AB_1$	TO PROCEED AND AND ADDRESS OF THE PERSON OF
	(i)	Introduction		583
	(ii)	Power output and distortion		583
	(iii)	The effect of power supply regulation	• • •	584
	(iv)	Matching and the effects of mismatching	• • •	584
	(v)	Average plate and screen currents	•••	584
	(vi)	Cathode bias	19.9.4	585
	(vii)	Parasitics		585
	(viii)	Phase inversion in the power stage	***	585
	(ix)	Extended Class A	***	587
	(x)	Partial triode ("ultra-linear") operation		587
7.	CLASS B A	MPLIFIERS AND DRIVERS	•••	587
- 50	(i)	Introduction		587
	(ii)	Power output and distortion-ideal conditions	—Class B	<sub>2</sub> 588
	(iii)	Power output and distortion-practical condition	ons—Class	B <sub>2</sub> 588
	(iv)	Grid driving conditions	(***)	590
	(v)	Design procedure for Class B <sub>2</sub> amplifiers	040414	592
	(vi)	Earthed-grid cathode coupled amplifiers		592
	(vii)	Class B <sub>1</sub> amplifiers—quiescent push-pull		592
R	` '	AMPLIFIERS		593
0.	(i)	Introduction		593
	(ii)	Bias and screen stabilized Class AB <sub>2</sub> amplifier		593
	(iii)	McIntosh amplifier		594
0	0.1 *0.70***********	OLLOWER POWER AMPLIFIERS		596
	SPECIAL FE	ANY CONTROL OF THE CO		596
10.		Grid circuit resistance	•••	596
	(i)		•••	597
	(ii)			598
	(iii)	Miler Effect	\$ <b>**</b> *	508
	(iv)	26 volt operation	D####	500
	(v)	Hum from plate and screen supplies	(*(*)*(*)	500
11.	COMPLETE		***	500
	(i)	Introduction		500
	(ii)	Design procedure and examples		600
	(iii)	Loudspeaker load	• • •	(01
12.	REFERENCES		• • •	601

SECTI										PAGE
	CH	APTER 14.	FIDE	LITY	AND	DIST	ΓORT	ION		
1.	Introduction	on			***		•••		((*****)	603
	(i)	Fidelity	1.000	* * *	•••		***	***		603
	(ii)	Types of di					***		• • •	604
	(iii)	Imagery for	describin	g reprod	duced	sound	***	***		604
2.	Non-Linea	R DISTORTIO	N AND H	ARMONIC	S					605
	(i)	Non-linearit	у	111	1.12		• • •		***	605
	(ii)	Harmonics		•••	***	20.00			• • •	606
	(iii)	Permissible			on	5 <b>5.25</b> 2	• • •	•••	•••	607
	(iv)	Total harmo			• • •		***	***	• • •	609
	(v)	Weighted d					•••		• • •	610
	(vi)	The search	for a tru	e criterio	on of i	non-lin	earity	• • •		610
3.	INTERMODU	LATION DIST	ORTION		• • •					611
	(i)	Introduction			•••	•••	•••		•••	611
	(ii)	Modulation	City and the contract of the c					•••	***	612
	(iii)	Difference f				n metl	nod		•••	613
	(iv)	Individual s				1.50	122.2		•••	613
	(v)	Modulation				t—pea	k sum	(*(*)*	***	614
	(vi)	Le Bel's os				2.434.63	***	•••	•••	614
	(vii)	Comparison					***	• • •	* * *	616 616
	(viii)	Synthetic b	ass	•••	•••	• • •	114			
4.	FREQUENCY	DISTORTION	***	12.20.2			•••		•••	617
	(i)	Frequency 1	273	0.90	***	***	•••	(35.5 (5.1)	•••	617
	(ii)	Tonal balan		1600		***	<b>€0€0€</b> 0	(*:•:•:	<b>4.5</b>	617
	(iii)	Minimum a		ange in	freque	ncy ra	nge			617
	(iv)	Sharp peaks	3	3000		***	****	***	***	618
5.	PHASE DIST	TORTION	***	***	(*)**	•••		•••	•••	618
6.	TRANSIENT	Distortion			***				•••	619
15.5%	(i)	General sur	vey		* * *		***	• • •	•••	619
	(ii)	Testing for	10.75 et	respons	e	***				619
_	Danisira I	DANIOR AND I	TO TIME	ATIONE						620
1.		RANGE AND I Volume ran			•••	• • •	***			620
	(i)	Effect of vo				r rang	 A			621
	(ii) (iii)	Acoustical 1			THE RESERVE THE PARTY OF THE PA					623
	(iv)	Volume ran	- Control of the Cont							623
	(v)	The effect					***	10.00 1.1.00	•••	624
_	3.5				4,65,0,95	V6V6VX	W. 15 1004			625
8.	Scale Dis			0.000	3.4.4.9		***	* * *	5.5 M	
9.	47.00 TATO A MANAGEMENT (201)	RMS OF DIST		PARAM	1000000 	***	***		*(*,*)	626
	(i)	Frequency-					7.4.k		¥34/42	626
	(ii)	Variation o	Pri manasana anni ana ana	cy respo	nse wi	tn out	put lev	eı	• • •	626 626
	(iii)	Listener fat	igue	\$.\$4\$.	• • • •	••	•••	• • •	•••	020
10.	FREQUENCY	RANGE PRE	FERENCES	•••	• • •			•••		627
	(i)	Tests by C	Chinn and	Eisenbe	erg	•••	•••	• • •		627
	(ii)	Tests by C					•••			627
	(iii)	Single chan		s dual-c	hannel	tests	25.55	***	•••	627
	(iv)	Summing u	qu	***	***	***	***	(*/*)*		628
11.	SPEECH RE	PRODUCTION	***	***	****	***	• • • •	***		628
-willer (2076)	(i)	The charac		of speech	1	*(*,*)	***	***	***	628
	(ii)	Articulation		***				***		628
	(iii)	Masking of							***	629
	(iv)	Distortion				• • •	• • •	•••	• • •	629
	(v)	Frequency	ranges fo	r speech	l	• • •	•••	•••	• • •	630

SECT	ION				PAGE
12.	HIGH FIDE	LITY REPRODUCTION			630
980,000,00	(i)	The target of high fidelity			630
	(ii)	Practicable high fidelity			630
	(iii)	The ear as a judge of fidelity			632
12		The car as a juage of money			632
13.	REFERENCES	*** *** *** *** ***	•••	•••	032
CH	ADTED 14	5. TONE COMPENSATION AND TON	E C	NT	ROI
CH			E C	JN I	
1.	Introducti	k의 호텔 Tubb Tubb Tubb Tubb Tubb Tubb Tubb Tu		• • •	635
	(i)	The purpose of tone compensation	• • •		635
	(ii)	Tone control	• • •		636
	(iii)	General considerations	•••	•••	636
	(iv)	Distortion due to tone control	• • •	•••	636
	(v)	Calculations involving decibels per octave	***	•••	637
	(vi)	Attenuation expressed as a time constant	***	***	638
	(vii)	The elements of tone control filters	• • •	•••	639
	(viii)	Fundamental circuit incorporating R and C			639
	(ix)	Damping of tuned circuits		• • •	639
	(x)	Tolerances of elements			639
2	Bass Boost	ring			640
ے.	(i)	General remarks			640
	(ii)	Circuits not involving resonance or negative feed			640
	(iii)	Methods incorporating resonant circuits			644
	(iv)	Circuits involving feedback			645
		Regeneration due to negative resistance characte			648
10200	(v)		HISTIC	1575702	
3.	BASS ATTE	TO SECULATION OF THE SECURATION OF THE SECULATION OF THE SECULATIO	• • •	•••	649
	(i)	General remarks	1.50%		649
	(ii)	Bass attenuation by grid coupling condensers	*0.000	08.8±*	649
	(iii)	Bass attenuation by cathode resistor by-passing	*****	•••	649
	(iv)	Bass attenuation by screen by-passing			650
	(v)	Bass attenuation by reactance shunting			650
	(vi)	Bass attenuation by negative feedback			651
	(vii)	Bass attenuation by Parallel-T network			651
	(viii)	Bass attenuation using Constant k filters			652
	(ix)	Bass attenuation using M-derived filters		• • •	652
4.	COMBINED	BASS TONE CONTROLS			653
	(i)	Stepped controls	***	* * *	653
	(ii)	Continuously variable controls	***		653
5.	TREBLE BO	9 to 1 to			653
	(i)	General remarks		1112	653
	(ii)	Circuits not involving resonance or negative fee			653
	(iii)	Methods incorporating resonant circuits			654
	(iv)	Cinavias invaluina foodbook			655
6	. Treble A		10:00	* * *	655
0.	***		15.005	***	655
	(i)	General remarks	300	***	655
	(ii)	Attenuation by shunt capacitance			657
	(iii)	Treble attenuation by filter networks			
_	(iv)	Treble attenuation in negative feedback amplifie	ers		657
7.	. COMBINED	TREBLE TONE CONTROLS			658
8	. Combined	BASS AND TREBLE TONE CONTROLS	36.004		658
	(i)	Stepped controls—general	0##/4		658
	(ii)	Quality switch		274	659
	(iii)	Universal step-type tone control not using indu			660
	(iv)	Universal step-type tone control using inductors			661
	(v)	Fixed bass and treble boosting		•••	662
		21570			

SECT	ION									PAGE
	(vi)	Step-type tone	control	using	negat	ive feed	lback	***		662
	(vii)	Continuously-var		100	N 50.700			• • •		662
	(viii)	Single control c	ontinuo	usly-v	ariable	e tone	contro	ols		662
	(ix)	Ganged continue	ously-va	ariable	tone	control	s		• • • •	664
	(x)	Dual control con	MANAGAMINANA 🕶 . NA ANTARA					s	•••	664
9		TO PROVIDE TONE	CONT	ROL.	200000	224	72227			669
	(i)	Introduction						•••		669
	(ii)	Amplifiers with	feedba							669
	(iii)	Whistle filters u								672
10		FREQUENCY-COM				CONTR	OT.			672
10.	(i)	Introduction	APENSAI			CONTR		•••		672
	(ii)	Methods incorp	orating	a tan	ned n	otention	 neter			672
	(iii)	Methods incorp	4-35			142		•••		673
	(iv)		orating					nsion	with	0.5
	(14)	multi-chann	a w				···		****	673
	W/		or ump		0 <b></b>					673
11.	WHISTLE F	Resonant circuit	filtore	• • •	•••			(.00€.0€.	***	673
	(i)	NT 18 1 1		filter	•••	***				675
	(ii)	Narrow band re	Particular Communication of the Communication of th		•••	•••	• • •	•••	• • •	675
	(iii)	Crystal filters Parallel-T netwo		•••	•••	•••	•••	•••	•••	675
	(iv)	Filters incorpora		and (	c	• • •	•••	•••	•••	676
	(v)					\$2.50°C	A. B. A.	***		88880.00
12.		THODS OF TONE			•••	•••	•••	•••	•••	676
	(i)	Multiple-channe	ı ampıı	ners	•••		• • •	•••	***	676
6575 255	(ii)	Synthetic bass	**************************************	(1000000000000000000000000000000000000		***	• • •	***	2 <b>.69.6</b> 7	676
13.	THE LISTE	NER AND TONE C	CONTROL	Ĺ	•••	•••	***	•••	•••	677
	EQUALIZER	Networks	•••			•••	•••	•••	•••	677
14.	Equalizer References		•••	•••		•••	•••	•••	•••	677 677
14. 15.	REFERENCE	16. VOLUMI	 E EX	 PANS	 SION		•••			
14. 15.	REFERENCE	16. VOLUMI		 PANS	 SION		•••	• • •		677
14. 15.	REFERENCE	16. VOLUMI	 E EX	 PANS	 SION		•••	• • •		677
14. 15.	REFERENCES	16. VOLUMI	E EX	 PANS ΓING	 SION	 , co	 MPR	• • •	 ON .	677 AND 679
14. 15.	REFERENCES  IAPTER  GENERAL I	16. VOLUMI PRINCIPLES	E EX	 PANS ΓING		 , co				677 AND 679 679
14. 15.	REFERENCES  IAPTER  GENERAL I  (i)	16. VOLUMI PRINCIPLES Introduction	E EX	 PANS ΓΙΝG 	SION	 , co 	MPR	 ESSIC	 ON	677
14. 15.	REFERENCES  IAPTER  GENERAL I  (i)  (ii)	PRINCIPLES Introduction An ideal system Practical problem Distortion	E EX	 PANS ΓΙΝG 	SION	 , co 	MPR	ESSIC	 ON 	677 AND 679 680
14. 15.	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)	PRINCIPLES Introduction An ideal system Practical problem	E EX	PANS FING	SION	   nsion	 MPR 	 ESSIC	  	677 AND 679 680 680
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)  (iii)  (iv)	PRINCIPLES Introduction An ideal system Practical problem Distortion General commen	E EX	PANS ΓING  volume	SION	   nsion 	 MPR	 ESSIC	 ON	677 AND 679 680 680 681
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (iv)  (v)	PRINCIPLES Introduction An ideal system Practical problem Distortion General commen	E EX	PANS FING	SION	   nsion 	 MPR	 ESSIC	 ON 	677 AND 679 680 681 681 681
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  Volume C  (i)  (ii)	PRINCIPLES Introduction An ideal system Practical problem Distortion General commen	E EX	PANS	SION	  nsion  	 MPR	 ESSIC	  	677 679 679 680 681 681
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  Volume C  (i)  (ii)  (ii)  (iii)	PRINCIPLES Introduction An ideal system Practical problem Distortion General commen	E EX	PANS	SION	     	 MPR	 ESSIC	  	677 679 679 680 681 681 681 681 682
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  Volume C  (i)  (ii)  (ii)  (iv)  (v)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Distortion cause	E EX LIMIT	PANS FING volume	 SION  e expa 	  nsion  	 MPR	 ESSIC	  	677 679 679 680 681 681 681 681
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  Volume C  (i)  (ii)  (ii)  (iv)  (v)  (v)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Distortion cause Volume compression	E EX LIMIT	PANS FING volume volume eak li	SION  c expa   miters	  nsion  	 MPR	 ESSIC	  	679 679 680 681 681 681 681 682 683
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  Volume C  (i)  (ii)  (ii)  (ii)  (iii)  (iv)  (v)  (	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Distortion cause Volume compress Volume compress	E EX LIMIT	PANS FING volume volume toeak li	SION  ce expa   miters  niting	 nsion    or vol	MPR	ESSIC	   	677 679 679 680 681 681 681 681 683 683 683 683
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  VOLUME C  (i)  (ii)  (ii)  (vi)  (vi)  (vi)  (vi)  (vi)  (vi)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Volume compression of	E EX LIMIT	PANS FING volume volume toeak li	SION  ce expa   miters  niting	 nsion    or vol	MPR	ESSIC	   	677 679 679 680 681 681 681 681 683 683 683
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  VOLUME C  (i)  (ii)  (ii)  (vi)  (vi)  (vi)  (vi)  (vi)  (vi)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Distortion cause Volume compress Volume compress Volume compress TROL DEVICES	E EX LIMIT	PANS PING volume volume tus lin ercial s	SION  ce expa   miters  niting	 nsion    or vol	MPR	ESSIC	   	677 679 679 680 681 681 681 681 683 683 683 683
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  (vi)  (iii)  (iv)  (vi)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Volume limiters Distortion cause Volume compres Volume compres Volume compres TROL DEVICES Remote cut-off	E EX LIMIT  ms in v  nts stion ssion ssion prode	PANS FING volume volume to eak li eak li excial s	SION  SION  E expa   miters  niting speech	 nsion   or vol	MPR	ESSIC	   	677 679 679 680 681 681 681 681 683 683 683 684 684
14. 15. CF	REFERENCES  IAPTER  GENERAL I  (i)  (ii)  (ii)  (iv)  (v)  (vi)  (ii)  (iv)  (vi)  (vi)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Volume limiters Volume compres Volume compres Volume compres Volume compres TROL DEVICES Remote cut-off Pentagrids and	E EX LIMIT  LIMIT  I I I I I I I I I I I I I I I I I I	PANS FING volume volume toeak line eak line e	SION  SION  E expa   miters  niting speech	 nsion   or vol	 MPR	ESSIC	  	677 AND 679 680 681 681 681 681 683 683 683 684 684 684 684
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  (vi)  (iii)  (iv)  (vi)  (vi)  (vi)  (vii)  GAIN CON  (i)  (ii)  (iii)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Volume limiters Volume compres	E EX LIMIT  LIMIT  I I I I I I I I I I I I I I I I I I	PANS FING volume volume toeak line eak line e	SION  SION  E expa   miters  niting speech	 nsion  or vol	 MPR	ESSIC	   	677 AND 679 680 681 681 681 681 683 683 683 684 684 684 684 684
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  (vi)  (vi)  (vi)  (vi)  (vii)  GAIN CON  (i)  (ii)  (iii)  (iv)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Volume limiters Volume compres	E EX LIMIT  LIMIT  I I I I I I I I I I I I I I I I I I	PANS FING volume volume toeak line eak line e	SION SION SION SION SION SION SION SION	or vol	 MPR	ESSIC	   	677 679 679 680 681 681 681 681 683 683 683 684 684 684 684 684 685 685
14. 15. CF	REFERENCES  HAPTER  GENERAL I  (i)  (ii)  (iii)  (iv)  (v)  (vi)  (iii)  (iv)  (vi)  (vi)  (vi)  (vii)  GAIN CON  (i)  (ii)  (iii)	PRINCIPLES Introduction An ideal system Practical problem Distortion General comment OMPRESSION Introduction Peak limiters Volume limiters Volume limiters Volume compres	E EX LIMIT	PANS FING  colume	SION  SION	or vol	 MPR	ESSIC	   	677 AND 679 680 681 681 681 681 683 683 683 684 684 684 684 684

SECTION								PAG
4. Volume Exp	PANSION	€0€/±0 3			•	•••	•••	68
	Introduction	***			••	• • •	•••	68
(ii)	Expanders incorporation	ng lamp	s .			•••	•••	68
(iii)	Expanders utilizing fe	edback			••	• • •	•••	68
(iv)	Expanders incorporation	ng remo	te cut-c	off pent	odes		•••	68
(v)	Expanders incorporation	ng remo	te cut-o	off triod	les			68
(vi)	Expanders incorporating	ng suppr	essor-gr	id cont	rolled	pento	odes	68
(vii)	Expanders incorporation	ng valve	s with	five gri	ds			69
(viii)	Expanders incorporation	ng plate	resistar	nce con	trol	•••		69
1883	=3/	F						69
5. Public Add	RESS A.V.C		•••	98089 1487	••			69
6. SPEECH CLI	PPERS	•••	•••	••	••	• • •	•••	
7 Noise Peak	AND OUTPUT LIMITER	S					•••	69
(i)	Introduction	***			••	•••		69
(ii)	Instantaneous noise p	eak limi	ters			7742816		69
(iii)	Output limiters					• • •	• • •	69
M255 AS	General remarks			89.6	• •			6
(iv)	Ocherat Telliarks	100			eren.	202020	) 1 <u>0</u> 00 <u>2</u> 02	6
8. References			***			5.5056		
					D.T.	SORT		
CHAP	TER 17. REPROI	DUCTI	ON F	ROM	KEC	COKI	73	
	ON TO DISC RECORDIN						****	7
22.2	Methods used in sou	nd recor	rdino				• • •	7
(i)					•••	•••		7
(ii)	Principles of lateral r						#X5	7
(iii)	Frequency range	 mamia <b>=</b>			•••		•••	7
(iv)	Surface noise and dy				•••	***		
( <b>v</b> )	Processing	•••		•••	• • •	***	1918.7	
(vi)	Turntables and drivi	ng mech	nanism	•••	•••			
(vii)	Automatic record cha	angers		•••	•••		* * *	
2. DISCS AND	A-MANAGAMANA		•••	•••		•••	***	8
(i)	General information	on discs	s	•••			•••	8
15(2)(7)(2)	Dimensions of record	ds and s	grooves					
(ii)						•••		
(iii)	Styli Pinch effect		•••	2.			•••	104
(iv)				: • • • ·	####### #############################	• • •	•••	J.
(v)	Radius compensation			72244	•••		• • •	•
(vi)	Record and stylus w	Cai			A TA			
3. PICKUPS			***	1000	•••		•••	
(i)	General survey	•••		# # #? ******	•••	• • •	***	
(ii)	Electro-magnetic (mo	oving ir	on) pick	<b>cups</b>	•••	***	•••	
(iii)	Dynamic (moving co	oil) pick	ups	***	•••	***	***	
(iv)	Piezo-electric (crysta	l) picku	ps	• • •		5.00		
(v)	Magnetostriction pic	kups	•••	•••	• • •	•••	•••	
(vi)	Strain-sensitive pick	ups			• • •	•••		
23 55	Ribbon pickups	***	•••	• • •	•••	•••	•••	
(vii)	Capacitance pickups			•••	•••	•••		
(viii)	Eddy-current pickup	os				•••	•••	
(ix)	162-2045-3810300 NS-0	9M 1467						
4. Tracking	*** ***			35.9.15	3.8.5	•••		
(i)	General survey of the	ne probl	iem		•••	***	1. T. T. T.	
(ii)	How to design for	minimu	m distor	tion		•••	• • •	
(iii)	The influence of sty	ylus fric	tion	***	•••	•••	***	
	- Та	UALIZER	s and A	MPLIFI	ERS	* * *		
5. RECORDING	Recording character	istics						
(i)	Pre-amplifiers for u	se with	pickup	s				ķ
(ii)	Pre-ampliners for u	olizano	pickup.					
(iii)	Introduction to equ	alizeis						
(iv)	High-frequency atte	nuation	(SCIALCI	kupe				
(v)	Equalizers for elect	ro-magn	etic pic	kups	• • •			h

SECTI	ION								PAGE
	(vi)	Equalizers for crystal p	pickups			•••	• • •	•••	741
	(vii)	Equalizers applying ne	gative i	feedbac	ck to t	he pic	kup	•••	743
	(viii)	Miscellaneous details r	egardin	g equa	alizing	amplif	iers		743
	(ix)	Complete amplifiers							744
	(x)	Pickups for connection			eivers	•••			751
	(xi)	Frequency test records							752
4	45 55 850 B	表 (2007) 2007(2007) (2007(2007)) (2007(200				0.2-2-20		19.50	
0.		AND UNDESTRABLE EFF	7,25	···	• • •			***	757
	(i)	Tracing distortion and	N-7-2	епест		***	***	* • •	757
	(ii)	Playback loss		181818 HAIR THAMBERT	•••	• • •			760
	(iii)	Wow, and the effects			ping				760
	(iv)	Distortion due to stylu	is wear		• • •		•••	• •	761
	(v)	Noise modulation	•	•••	• • •	•••	• • •	• • •	761
	(vi)	Pickup distortion		•••	5.5.5		•••		762
	(vii)	Acoustical radiation	****		***				762
	(viii)	Distortion in recording	3	• • •		*:*:*:			762
7	Noise Red	UCTION							763
	(i)	Analysis of noise		27.5		******			763
	(ii)	High-frequency attenua	ation	***	•••	• • •	V\$9\$(\$6)	• • •	763
	(iii)	High-frequency pre-en		and d	 la amn'	hacie		***	763
	2. 5		(6.5		6350		***	***	
	(iv)	Volume expansion			• • •	• • •			763
	(v)	Olson noise suppressor		•••	•••				763
	(vi)	Scott dynamic noise si			•••	•••	• • •	•••	764
	(vii)	Price balanced clipper				•••	•••	• •••	765
8.	LACQUER I	DISC HOME RECORDING	(Direct	PLAY	BACK)			• • •	766
	(i)	General description	•						766
	(ii)	Recording characteristi	С		•••			•••	766
	(iii)	Cutting stylus		***				•••	767
	(iv)	Cutter head			• • •				767
	(v)	Equalization of cutter				***			767
	(vi)	Motor and turntable	020		222		222		767
	(vii)	Amplifier					2000		767
	(viii)	Pickups for use on lac							768
	(ix)	Recording with embos	일반하다면 그렇게 얼마 하다?			•••		•••	768
0	130.5543404	Activities appropriate the Committee of					5.5		
9.		ION FROM TRANSCRIPTIO	אנום אנ	LS.	• • •	• • •	•••	• • •	769
	(i)	Introduction	•••	• • •	• • •		•••	• • •	769
	(ii)	Characteristics of reco	ra mate	eriai, v	wear ar	na nois	se	***	769
	(iii)	Sound track			. •••	***		****	770
	(iv)	Recording characteristi					* * *		770
	(v)	Translation loss and r	adius c	ompen	isation				770
10.	REFERENCE	TO LATERAL DISC REC	CORDING	i		•••			771
	CHA	PTER 18. MICRO	PHON	ES, I	PRE-A	MPL	IFIEF	RS,	
		ATTENUATO	RS A	ND M	MIXE	RS			
1.	Micropho			100		OF STATES	888	****	775
	(i)	General survey		#:#9#8			***	***	775
	(ii)	Carbon microphones		•••	•••		***		777
	(iii)	Condenser microphone			***	***			778
	(iv)	Crystal and ceramic n		ones					778
	(v)	Moving coil (dynamic			s				779
	(vi)	Pressure ribbon micro				1000			779
	(vii)	Velocity ribbon micro	-						779
	(viii)	Throat microphones		223			•••		780
	(ix)	Lapel microphones		•••				***	780
	(x)	Lip microphones		•••	•••	8755	***	***	780
	(/		257				# #5#	•••	100

(xxvii)

	TOTAL	N TO	
CON	NIE	N	13

	M							
CTIO	(xi)	The directiona	l characte	ristics of	micropl	ones	•••	• • •
	(xii)	The equalizati	on of mic	rophones			***	
	(xiii)	Microphone to	ansformer	s			•••	
	(xiv)	Standards for	microphor	nes	***		•••	***
	88 - 0.50							
2.	Pre-Ampli	Introduction				•/•		
	(i)					10.0		
	(ii)			***			•••	
	(iii)	Hum		•••				
	(iv)	Microphony Valves for use		mnlifiers		****	•••	
	(v)	Microphone p				59596		
	(vi)	Pickup pre-an						1.000
	(vii)	Gain-controlle						0.00
	(viii)	Standard pre-						• • •
	(ix)	Standard pre-						
	(x)		73 SW	101 3041	ia cquip	IIICIIL		
3.	ATTENUAT	ORS AND MIXER	S					¥.(¥.(¥.)
	(i)	Potentiometer	type atte	nuators	volume	controls)	•••	• • •
	(ii)	Single section	attenuato	rs—cons	tant imp	edance		
	(iii)	Single section a	ttenuators-	-constan	nt impeda	nce in or	ne dire	ction
	12	only	•••				•••	***
	(iv)	Multiple sect	ion attenu	ators	. In Contract	***	• • •	***
	(v)	Electronic att	enuators					• • •
	(vi)	Mixers and f	aders-ger	neral		activo	100000	
	(vii)	Non-constant	impedanc	e mixers	and fad	ers		
	(viii)	Constant imp	adanca mi	vers and	faders			
	REFERENCE	is	FOR 7	 ГНЕ М	MEASU	 REMEN	 VT (	 )F G
	REFERENCE	is	FOR 7	343414 343	MEASU	 REMEN	 VT (	
	REFERENCE	19. UNITS	FOR AND	THE NOIS	MEASU E	taxille.		)F G
	REFERENCE	19. UNITS  DECIBELS Power relation	FOR AND	THE NOIS	MEASU E	 nd decib	 els	)F G 
	REFERENCE APTER BELS AND (i)	19. UNITS  DECIBELS  Power relation Voltage and	FOR AND	THE NOIS	MEASU E  in bels a	 nd decib	 els lecibel	)F G 
	REFERENCE  APTER  BELS AND	DECIBELS Power relation Voltage and Absolute power	FOR AND	THE NOIS	MEASU E  in bels a ps expres	 nd decib ssed in o n decibe	 els lecibel	)F G
	REFERENCE APTER  BELS AND (i) (ii)	DECIBELS Power relation Voltage and Absolute power Microphone	FOR AND	THE NOIS  Oressed  clationship	MEASU E in bels a ps expres pressed	 nd decib ssed in o n decibe	 els lecibel	OF G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iii)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output	FOR AND onships experient recorded and version and version and version at expressed	THE NOIS  NOIS  pressed  lationshi  oltage ex  pressed  d in de	MEASU E  in bels a ps expre- pressed in decibe	 nd decib ssed in o n decibe	 els lecibel els	)F G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iii) (iv)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas	FOR AND onships experience and version expressed in expressed	THE NOIS  NOIS  Interpressed in deced in deced in deceded in deced	MEASU E in bels a ps expres pressed in decibe cibels cibels	 nd decib ssed in o n decibe ls	 els lecibel ls 	OF G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (v)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mi	FOR AND onships exponent recorded to expressed to expressed crophone and expressed crophone	THE NOIS  NOIS  pressed  lationshi  oltage ex  ed in de	MEASU E in bels a ps expres pressed in decibe cibels cibels cibels	nd decibersed in	 els lecibel ls 	OF G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (v) (vi)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined microphone Loudspeaker	FOR AND onships exponent recorded to the expressed output	THE NOIS  Pressed  Interpressed  In deed in de	MEASU E in bels a ps expres pressed in decibe cibels cibels cibels	nd decibersed in	 els lecibel ls 	OF G
	REFERENCE  APTER  BELS AND  (i)  (ii)  (iii)  (iv)  (vi)  (vi)  (vii)  (viii)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined microphone Loudspeaker Sound system	FOR AND onships exponent recorded to expressed to expressed to output expressed to	THE NOIS  Pressed  Interpressed  In deed in de	MEASU E in bels a ps expre- pressed in decibe cibels cibels cibels ifier gain in decibe	nd decibersed in decibers of decibers of the contract of the c	els lecibel ls 	oF G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vi) (vii) (viii) (viii) (ix)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and	FOR AND onships exponent recorded to expressed to expressed to complete expressed to expressed t	rHE NOIS  NOIS  pressed  lationshi  oltage ex  pressed  in de  and ampl  apressed  in de  chind ampl	AEASU  E  In bels a  ps expres  pressed  in decibe  cibels	nd decibersed in decibers of decibers of the contract of the c	els lecibel ls  d in de	oF G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vi) (vii) (viii) (viii) (ix) (x)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and Nomogram	FOR AND onships exponent recorded and version expressed output expressed o	ressed in deed in decibel ressed	AEASU  E  In bels a  ps expres  pressed  in decibe  cibels  ci	nd decibersed in decibers of decibers of the contract of the c	els lecibel ls  d in de	oF G
	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vi) (vii) (viii) (viii) (xi) (xi) (xi)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and	FOR AND onships exponent recorded and version expressed output expressed o	ressed in deed in decibel ressed	AEASU  E  In bels a  ps expres  pressed  in decibe  cibels  ci	nd decibersed in decibers of decibers of the contract of the c	els lecibel ls  d in de	oF G
1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vi) (vii) (viii) (viii) (xii) (xi) (xii)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slices	FOR AND  onships exponent recorded and expressed crophone and coutput expressed crophone and charts of office adding the rules are	THE NOIS  NOIS  Pressed  Idiana de  Idiana d	AEASU  E  In bels a  ps expres  pressed  in decibe  cibels  cibels  cibels  cibels  cibels  cibels  cibels  and decibe  cibels  cibels	nd decibersed in decibers of decibers of the contract of the c	els lecibel ls  d in de	oF G
1.	REFERENCE APTER  BELS AND (ii) (iii) (iii) (iv) (vi) (vii) (viii) (viii) (ix) (xi) (xii) (xii) VOLUME	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slient Indicators and I	FOR AND onships exponent recorded and version expressed output expressed o	THE NOIS  NOIS  Pressed  Interpressed  In desired in desired in desired  Indicated in desired in desired  Indicated in desired in desired  Indicated in desired in de	MEASU  E  In bels a  ps expres  pressed  in decibe  cibels  cibels  cibels  cibels  cibels  cibels  cibels  al arithm	nd decibers of decibers of decibers of the contract of the con	els lecibel ls  d in de	oF G
1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vii) (viii) (viii) (ix) (xi) (xii) (xii) VOLUME (i)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slice Indicators and Volume indicators and Volume indicators and Nomogram of Decibels, slice Indicators and Volume indicato	FOR AND  onships exponent recorded and expressed output e	rHE N NOIS neessed lationship oltage ex pressed ed in de ed ed in de ed ed in de ed in de ed in de ed ed e	AEASU  In bels a ps expressed in decibels cibels cibels in decibe cibels in decibe cibels arithmeter gain arithmeter gain in decibe cibels cib	nd decibers of dec	els lecibel ls  d in de 	oF G
2.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vii) (vii) (viii) (ix) (xi) (xii) VOLUME (i) (ii)	DECIBELS Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slice Indicators and Volume indicators and Volume indicators and Volume unit	FOR AND  onships exponent recorded and expressed output e	THE NOIS  NOIS  Pressed  Idian de  I	MEASU  E  In bels a  ps expres  pressed  in decibe  cibels  cibels  cibels  cibels  cibels  cibels  cibels  al arithm	nd decibers of dec	els lecibel ls  d in de 	oF G
2.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vii) (vii) (viii) (ix) (xi) (xii) VOLUME (i) (ii)	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slice Indicators And Volume indicators and Volume unit NG INSTRUMENT	FOR AND  onships exponent recorded expressed output expre	THE NOIS  NOIS  pressed  lationshi  oltage ex  pressed  in de  de in de  and ampl  pressed  decibel  decibel  nd ment  UNITS	AEASU  In bels a ps expressed in decibels cibels cibels in decibe cibels in decibe cibels arithmeter gain arithmeter gain in decibe cibels cib	nd decibers of dec	els lecibel ls  d in de 	OF G s cibles
CH 1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vii) (vii) (viii) (ix) (xi) (xii) VOLUME (i) (ii)	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gas Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slick Indicators and Volume individual Volume unit NG Instrument Decibel met	FOR AND  onships exponent recorded and expressed output e	THE NOIS  NOIS  pressed ed in deed in deed in decibel ressed clecibel ressed conditioners  decibel respectively  decibel ressed	AEASU  E  In bels a  ps expres  pressed  in decibe  cibels  cibels  cibels  cibels  cibels  cibels  al arithm	nd decibersed in decibers in d	els lecibel ls  d in de 	oF G
CH 1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vii) (viii) (viii) (viii) (xi) (xi) (xii) VOLUME (i) (ii) INDICATI	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slice Indicators And Volume indicators and Volume indicators and Volume unit NG INSTRUMENT Decibel met Power output	FOR AND  onships expense output expressed output expressed output expressed output expressed output expensed output expressed	THE NOIS  NOIS  pressed ed in deed in decibel ressed condamples condecibel ressed condamples condam	MEASU E  In bels a ps expres pressed in decibe cibels cibels cibels cibels cibels al arithm expressed al arithm	nd decibersed in decibers in d	els lecibel ls d in de ties	OF G s cibles
CH 1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vii) (viii) (viii) (viii) (xii) VOLUME (i) (ii) INDICATION (ii) (ii)	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram of Decibels, slick Indicators and Volume indicators and Volume unit NG INSTRUMENT Decibel met Power output Volume indicators and Nomogram of Nom	FOR AND  onships expense output expresse output expresse of of adding the rules are cators  or adding the rules are cators	THE NOIS  OPPESSED  Interpolationship  Interpolationship  Interpolation decided in decid	MEASU E  In bels a ps expressed in decibels cibels cibels in decibe cibels in decibe cibels in decibe cibels in decibe cibels ci	nd decibersed in decibers in d	els lecibel ls  d in de 	oF G s cibles
CH 1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vi) (vii) (vii) (viii) (ix) (xi) (xii)  VOLUME (i) (ii) (iii) (iii)	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram Decibels, slice Indicators And Volume indicators and Volume indicators and Volume unit NG INSTRUMENT Decibel met Power output	FOR AND  onships expense output expresse output expresse of of adding the rules are cators  or adding the rules are cators	THE NOIS  OPPESSED  Interpolationship  Interpolationship  Interpolation decided in decid	MEASU  E  In bels a  ps expres  pressed  in decibe  cibels  cibels  cibels  ifier gain  in decibe  elationsh  expressed  al arithm	nd decibersed in decibers in d	els lecibel ls d in de ties	oF G s cibles
CH 1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vii) (viii) (viii) (viii) (xii) VOLUME (i) (ii) (iii) (iii) (iii) (iv)	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram of Decibels, slight Volume individume unit NG INSTRUMENT Decibel met Power output Volume individume	FOR AND  onships expense output expresse output expresse of output expresse output expresse output expresses of output expresses output expresse	THE NOIS  NOIS  pressed in desired in decibel ressed in decibel re	MEASU E  In bels a ps expressed in decibe cibels cibels cibels cibels cibels al arithm compressed al arithm	nd decibers of dec	els lecibel ls d in de ties	oF G s cibles
CH 1.	REFERENCE APTER  BELS AND (i) (ii) (iii) (iv) (vii) (viii) (viii) (viii) (xii) VOLUME (i) (ii) (iii) (iii) (iii) (iv)	DECIBELS  Power relation Voltage and Absolute power Microphone Pickup output Amplifier gast Combined mit Loudspeaker Sound system Tables and Nomogram of Decibels, slick Indicators and Volume indicators and Volume unit NG INSTRUMENT Decibel met Power output Volume indicators and Nomogram of Nom	FOR AND  onships expense output expresse output expresse of output expresse ou	THE NOIS  NOIS  pressed in desired in decibel ressed in decibel re	MEASU  E  In bels a  ps expres  pressed  in decibe  cibels  cibels  cibels  cibels  cibels  cibels  al arithm	nd decibers of dec	els lecibel ls d in de ties	oF G s cibles

SECT	ION							PAGE
5.	LOUDNESS		• • •				•••	826
	(i)	Introduction to loudne	SS	•••	• • •	• • •	•••	826
	(ii)	The phon	***	2.2.2	• • •		• • •	826
	(iii)	Loudness units	9.535	****		***	***	827
6.	THE MEAS	UREMENT OF SOUND LEV	EL AND	Noise	i	•••		827
	(i)	Introduction		•••			•••	827
	(ii)	The sound level meter				•••		828
	(iii)	The measurement of n	oise in	ampli	fiers			829
	(iv)	The measurement of r	adio no	oise		•••	•••	829
7.	REFERENCES	· · · · · · · · · · · · · · · · · · ·					***	830
		OHADTED OO	TOU	Don	A TZ T	D.C		
		CHAPTER 20.	LOU	DSPE	AKE	K2		
1.	INTRODUCT	ION					arae.	831
	(i)	Types of loudspeakers						831
	(ii)	Direct radiator loudspe		222	***		***	831
	(iii)	Horn loudspeakers						832
	(iv)	Headphones						832
	(v)	Loudspeaker characteri						933
	(vi)	Amplitude of cone mo				• • •		834
	(vii)	Good qualities of loud				***	3.375	834
	(viii)	Loudspeaker grilles	speaker			****	***	935
2		ISTICS OF MOVING-COIL	Cove	Loupe			•••	835
۷.		[2011년] [2012년 - 1202년						835
	(i)	Rigid (piston) cone in Practical cones	an mi	iiiic ii	at Dali	ic	•••	
	(ii)		on mide	····			• • •	835
	(iii) (iv)	Special constructions for		. <del></del>	10.50	_	***	836
	42	Impedance and phase			•••	•••	•••	020
	(v) (vi)	Frequency response	• • •	•••	•••	• • •	• • •	
	(vii)	Efficiency	ion	•••	1600	•••	***	839
	2	Directional characterist	ics	(######	***	***	***	839
	(viii)	Field magnet		• • •	• • •	7.4.4.4		840
	(ix)	Hum bucking coil	***			***		840
_	(x)	Damping		4		•••	•••	840
3.		D ENCLOSURES FOR DIREC	CT-RAD	IATOR .	Loudsi	PEAKERS		842
	(i)	Flat baffles			***	•••	• • •	842
	(ii)	Open back cabinets		•••		•••	•••	842
	(iii)	Enclosed cabinet louds					•••	843
	(iv)	Acoustical phase invert	Section 2017 Section 1		baffle '	")	•••	845
	(v)	Acoustical labyrinth lo	udspeak	<b>kers</b>		•••	•••	850
	(vi)	The R-J loudspeaker	•••	•••	36.00	***		850
	(vii)	Design of exterior of o	cabinet			***		850
	4. Horn	LOUDSPEAKERS	• • •	(*****	***	***	***	851
	(i)	Introduction	****	***		•••		851
	(ii)	Conical horns	***					851
	(iii)	Exponential horns	222	• • •				851
	(iv)	Hyperbolic exponential				•••	• • •	853
	( <b>v</b> )	Horn loudspeakers—ge		•••		• • •	•••	854
	(vi)	Folded horn loudspeak		•••	(*:*:*	•••	•••	856
	(vii)	High-frequency horns		0*0***		•••	* * *	858
	(viii)	Combination horn and p	hase inv	verter lo	oudspe	akers fo	or perso	
	1050 83	radio receivers	***		(* * *			859
	(ix)	Material for making ho	orns				• • •	859
5.	DUAL AND	TRIPLE SYSTEM LOUDSP	PEAKERS	/			***	860
	(i)	Introduction				*** 1	***	860
	(ii)	Choice of the cross-ove	er frequ	uency				860

SECT	ION		10-01-00-0						PAGE
	(iii)	The overlap reg	gion		***	•••	• • •		861
	(iv)	Compromise arr	rangement	:s	• • •	•••	•••	•••	861
6.	LOUDSPEAK	ERS IN OPERATIO	N		•••	•••	•••	•••	861
	(i)	Loudness			***	•••	•••	•••	861
	(ii)	Power required	***			(*)*(*)	19.00	•••	861
	(iii)	Acoustics of roo		* ***				***	864
	(iv)	Loudspeaker pl		***	ecc			•••	865
	(v)	Stereophonic re			***	5 <b>****</b> 3	***	• • •	865
	(vi)	Sound reinforci	51 <del>00</del> 45 UT-010		•••			•••	866
	(vii)	Open air Public			1124172	***	•••	***	867
	(viii)	Inter-communic	있는데 15시간 (Marie - Marie 1987) (Marie 1987)		•••	• • •		• • •	867 867
	(ix)	Background mu	sic in fac	tories	•••	•••	•••	•••	
7.	DISTORTION	( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( )	RS		***			• • •	868
	(i)	Non-linearity	::			87.00	***		868
	(ii)	Frequency-mod		stortion	in louds	peakers	•••	•••	869
	(iii)	Transient distor			( <b>***</b>	•••	•••	***	869
	(iv)	Sub-harmonics		(C. 10)		1000	:00000	***	871 871
	(v)	Intermodulation							
8.	SUMMARY O	OF ACOUSTICAL I		• •••	•••			•••	871
	(i)	Definitions in a				•••	•••	•••	871
	(ii)	Electrical, mech		and the second s	500	valents	• • •	•••	872
	(iii)	Velocity and wa	evelength	of sound	1	6. O.			872
	(iv)	Musical scales	• •		***		•••	***	873
9.	STANDARDS	FOR LOUDSPEAK	ERS				•••	***	874
	(i)	Voice coil impe				•••	•••		874
	(ii)	Loudspeaker sta	andard ra	tings for	sound o	equipme	ent	***	874
Jugarias	APTER 2		•	BETW			 OWE	 R VA	876 LVE
	•								990
1.		er " Matching'			 natahina	•••		•••	880 880
	(i)	Loudspeaker ch							880
	(ii) (iii)	Optimum plate Procedure for	'matchin	e e" loud		to vario		es of	000
	(111)	amplifiers				···			881
_	11	100	T ovenopra						882
2.		AND EXTENSION	erweighte mer man kontra er skrive		•••	•••	•••		882
	(i)	Multiple loudsp			•••	•••	•••		883
	(ii) (iii)	Sound systems Extension louds	neakers		***	775A	1545.4543		883
	(iv)	Operation of lov	pcancis ideneakers			from an	nlifier	1555	886
2	1876 X77	The second second	120	at long c	istuitees	110111 411	pinici	•••	887
		ER DIVIDER NET	WORKS	OF 15.55	#15°.45	10,1130	S****	144000	
4.	REFERENCES	•••	**************************************	•••	•••	•••	• • •	•••	889
	CHAPT	PART 4: ER 22. AERI	12				N LI	NES	
1.	INTRODUCT	ION	[80.000 1020		***				890
2	THE TRANS						**************************************		890
۷,	THE TWINS	CWICCIUM I INTE						80.000	
	(i)	7 <u>2</u>	SP460 955		150505	#1550FC	2004/24/25		
	(i) (ii)	Introduction The correct ter	 mination		 ınsmissio	n line	•••	***	890 890

3.	A PRIATE AN	ND POWER TRANSFER	R					
	MERIALS A		N-8 00 (N-0)	7.00	• • •	100		
	(i)	Introduction						
	(ii)	Power transfer					•••	10.00
4.	CHARACTER	ISTICS OF AERIALS			•••		1.5.5.5.2	
	(i)	Effective area of a	receiving	aerial		5.55		
	(ii)	The power gain o	f an aeria	1	•••	***		
	(iii)	The beam-width of	of an aeri	al				
5.	EFFECTS OF	님 - [] 전시됐어? []() - []([[]() []() []() [[]() []() []() [[]() []()					***	
	(i)	Introduction						
	(ii)	A perfectly-conduc			222			
	(iii)	An imperfectly co	2000 NOTE NO.					
	(iv)	The attenuation of						ner-
	(-,)	fectly-reflectin	g earth				all IIII	per-
5.	THE EFFEC	T OF THE IONOSPHER			ION OF	Panto S	CONTAC	•••
		DANCE OF AN AERIAI		KECEP I	ION OF	KADIO S	IGNAL:	<b>.</b>
	(i)	Introduction		•••	• • •			• • •
	(ii)		481 Agricultura		* * *	* * *	•••	•••
	(iii)	Resistive compone	nt of imp	cuance		•••	•••	•••
	381,611,733,53	Reactive componer	nt of imp	edance	•••	****	•••	• • •
	(iv)	Characteristic imp		aerial			***	• • •
	(v)	Examples of calcu	rations	• • •	200	(******	•••	***
	(vi)	Dipoles	• •••	•••	*.*.*.			•••
	(vii)	Loop aerials		***			***	•••
3.	DUMMY A	그렇게 어린 경에 가지 않는데 그렇게 되었다.		1040 1040				
		AERIAL USED FOR B	ROADCAST	RECEPT	TION	1000		• • •
	(i)	Introduction			•••			
	/::/	Medium-fraguence	receiving	aerial	S			****
	(ii)	Medium-frequency	receiving					
	(iii)	Short-wave receiving	ng aerials					***
	(iii) (iv)	Short-wave receiving V-H-F aerials	ng aerials	•••	***	***	***	***
	(iii)	Short-wave receiving V-H-F aerials	ng aerials				•••	•••
	(iii) (iv) REFERENCES	Short-wave receiving V-H-F aerials	ng aerials	•••	51.51 51.51 54.51	***	***	•••
	(iii) (iv) REFERENCES	Short-wave receiving V-H-F aerials TER 23. RADI	ng aerials	•••	51.51 51.51 54.51	***	***	•••
	(iii) (iv) REFERENCES CHAP	Short-wave receiving V-H-F aerials TER 23. RADI	ng aerials	  QUEN	51.51 51.51 54.51	  MPLII	FIERS	···
	(iii) (iv) REFERENCES CHAP	Short-wave receiving V-H-F aerials TER 23. RADI	ng aerials O FRE	 UEN	 CY A	  MPLII	FIERS	··· ···
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i)	Short-wave receiving V-H-F aerials TER 23. RADI	ng aerials O FREC	 UEN 	 CY A	  MPLII 	FIERS	····
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i) (ii)	Short-wave receiving V-H-F aerials TER 23. RADION Aerial coupling Tuning methods	ng aerials	 UEN 	 CY A	 MPLII  	FIERS	····
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i) (ii) (iii) (iv)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design considerations	ng aerials O FREC	 QUEN  	 CY A	 MPLII  	FIERS	····
	(iii) (iv) REFERENCES CHAP INTRODUCTI (i) (ii) (iii) (iii) (iv) AERIAL STA	Short-wave receiving V-H-F aerials  TER 23. RADI ON  Aerial coupling Tuning methods R-F amplifiers  Design considerations	ng aerials O FREC	 UEN  	 CY A	 MPLII   	FIERS	····
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i) (ii) (iii) (iii) (iv) AERIAL STA	Short-wave receiving V-H-F aerials  TER 23. RADI ON  Aerial coupling Tuning methods R-F amplifiers  Design considerations  Difficulties involved	ng aerials O FREC	 QUEN  	 CY A	 MPLII  	FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i) (ii) (iii) (iv) AERIAL STA (i) (ii)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling	ng aerials O FREC	 QUEN  	 CY A	 MPLII   	FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT  (i) (ii) (iii) (iv)  AERIAL STA (i) (ii) (ii) (iii)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design considerations GES Difficulties involved Generalized coupling Mutual inductance	ng aerials O FREC	 QUEN  	 CY A	 MPLII   	 FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i) (ii) (iii) (iv)  AERIAL STA (i) (ii) (ii) (iii) (iv)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design consideration Ges Difficulties involved Generalized coupling Mutual inductance Tapped inductance	ng aerials O FREC	 QUEN   	 CY A	 MPLII   	 FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT  (i) (ii) (iii) (iii) (iv)  AERIAL STA (i) (ii) (iii) (iii) (iv)  (v)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling	ng aerials O FREC	 WEN	 CY A	 MPLII   	 FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT: (i) (ii) (iii) (iv) AERIAL STA (i) (ii) (iii) (iv) (vi) (vi) (vi)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary	ng aerials O FREC	 WEN	 CY A	 MPLII   	 FIERS	
	(iii) (iv) REFERENCES CHAP INTRODUCTI (i) (ii) (iii) (iii) (iv) AERIAL STA (i) (ii) (iii) (iv) (vi) (vi) (vi) R-F AMPLI	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS	ng aerials O FREC	 QUEN    	 CY A	 MPLII   	 FIERS	
	(iii) (iv) REFERENCES CHAP  CHAP  INTRODUCTO (ii) (iii) (iii) (iv) AERIAL STA (i) (iii) (iii) (iii) (iv) (vi) (vi) (v	Short-wave receiving V-H-F aerials  TER 23. RADI  ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using	ons	 WEN	 CY A	 MPLII	 FIERS	
	(iii) (iv) REFERENCES CHAP  CHAP INTRODUCTI (i) (ii) (iii) (iv) AERIAL STA (i) (iii) (iii) (iv) (vi) (vi) (vi) R-F AMPLI (i) (ii) (ii)	Short-wave receiving V-H-F aerials  TER 23. RADI ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using Mutual-inductance	ons	 WEN	 CY A	 MPLII	 FIERS	
	(iii) (iv) REFERENCES CHAF  CHAF  INTRODUCT (i) (ii) (iii) (iv) AERIAL STA (i) (iii) (iv) (vi) (vi) (vi) R-F AMPLI (i) (ii) (iii) (iii)	Short-wave receiving V-H-F aerials  TER 23. RADI  ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using Mutual-inductance Parallel tuned circum	ons ons ons ons r-f stage	 WEN	 CY A	 MPLII	FIERS	
	(iii) (iv) REFERENCES CHAP  CHAP INTRODUCT (i) (ii) (iii) (iv) AERIAL STA (i) (iii) (iii) (iv) (vi) (vi) R-F AMPLI (i) (ii) (ii) (ii) (iii) (iv) (vi)	Short-wave receiving V-H-F aerials  TER 23. RADI ON  Aerial coupling Tuning methods R-F amplifiers  Design consideration GES  Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS  Reasons for using Mutual-inductance Parallel tuned circue Choke-capacitance	ons  ons  ons  ons  r-f stage  coupling  coupling  coupling  coupling  coupling	UEN tage	 CY A	 MPLII	FIERS	
	(iii) (iv) REFERENCES CHAF  CHAF  INTRODUCT (i) (ii) (iii) (iv) AERIAL STA (i) (iii) (iv) (vi) (vi) (vi) R-F AMPLI (i) (ii) (iii) (iii)	Short-wave receiving V-H-F aerials  TER 23. RADI  ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using Mutual-inductance Parallel tuned circum Choke-capacitance Untuned and pre-terms	ons  ons  ons  r-f stage  coupling  coupling  coupling  coupling  coupling  coupling  coupling	UEN tage	CY A	 MPLII	FIERS	
	(iii) (iv) REFERENCES CHAP  CHAP INTRODUCT (i) (ii) (iii) (iv) AERIAL STA (i) (iii) (iii) (iv) (vi) (vi) R-F AMPLI (i) (ii) (ii) (ii) (iii) (iv) (vi)	Short-wave receiving V-H-F aerials  TER 23. RADI  ON Aerial coupling Tuning methods R-F amplifiers Design consideration GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using Mutual-inductance Parallel tuned circum Choke-capacitance Untuned and pre-terms	ons  ons  ons  r-f stage  coupling  coupling  coupling  coupling  coupling  coupling  coupling	QUEN tage	CY A	MPLII	FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT (i) (ii) (iii) (iv) AERIAL STA (i) (iii) (iv) (vi) (vi) R-F AMPLI (i) (ii) (ii) (vi) (vi) (vi) (vi) (vi)	Short-wave receiving V-H-F aerials	ons  r-f stage coupling	QUEN tage	CY A	 MPLII	FIERS	
	(iii) (iv) REFERENCES CHAP INTRODUCT (i) (ii) (iii) (iii) (iii) (iii) (iii) (iii) (iv) (vi) R-F Ampli (i) (ii) (ii) (ii) (ii) (vi) (vi) Image Rejected	Short-wave receiving V-H-F aerials  TER 23. RADI  ON Aerial coupling Tuning methods R-F amplifiers Design considerations GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using Mutual-inductance Parallel tuned circum Choke-capacitance Untuned and pre-tagrounded grid stage CTION	ons  r-f stage coupling	Cage	CY A	MPLII	FIERS	
	(iii) (iv) REFERENCES  CHAP  INTRODUCT (i) (ii) (iii) (iii) (iv) AERIAL STA (i) (iii) (iv) (vi) (vi) R-F AMPLI (i) (ii) (iii) (vi) (vi) IMAGE REJE (i)	Short-wave receiving V-H-F aerials  TER 23. RADI  ON	ons  r-f stage coupling coupling coupling coupling coupling coupling rejection rejection	CUEN  Control  Contro	CY A	MPLII	FIERS	
	(iii) (iv) REFERENCES CHAP INTRODUCT (i) (ii) (iii) (iii) (iii) (iii) (iii) (iii) (iv) (vi) R-F Ampli (i) (ii) (ii) (ii) (ii) (vi) (vi) Image Rejected	Short-wave receiving V-H-F aerials  TER 23. RADI  ON Aerial coupling Tuning methods R-F amplifiers Design considerations GES Difficulties involved Generalized coupling Mutual inductance Tapped inductance Capacitance coupling General summary FIERS Reasons for using Mutual-inductance Parallel tuned circum Choke-capacitance Untuned and pre-tagrounded grid stage CTION	ons  ons  ons  r-f stage coupling coupling coupling coupling coupling rejection e to aeria	WEN  Cage  Control  C	CY A	MPLII	FIERS	

SE

SECT	ION									PAGE
5.	EFFECTS OF	VALVE INPUT ADM	MITTAN	CE			•••			927
	(i)	Important general					•••		• • •	927
	(ii)	Input loading of r	eceivir	ig valve	es at	radio	freque	ncies		928
		(A) Input cor	nducta	nce .	• •	•••			*	929
		(B) Cold inpu	ut con	ductano	ce	•••	(*)*:*		•••	929
		(C) Hot inpu								930
		(D) Change is				e			***	932
		(E) Reduction	20.00	1000 CC						933
•	37 asm	CIRCUIT NOISE		3.5	4 5000	5.55				935
0.				••	••	•••	•••		***	935
	(i)	Thermal agitation			• •	• • •	***	• • •	• • •	936
	(ii)	Shot noise					•••	***	***	939
	(iii)	Induced grid noise			••	• • •	•••	• • •		940
	(iv)	Total noise calcula			••	•••	• • •		• • •	941
	(v)	Sample circuit cal	culatio	ons .	••	0.530	•••	• • •	•••	
	(vi)	Conclusions	• • •		• •	•••	***	•••	•••	942
7.	INSTABILIT	Y IN R-F AMPLIFIE	ERS .		••		•••			942
	(i)	Causes of instabili	ity .				•••		•••	942
	(ii)	Inter-electrode cap	pacitan	ice coup	pling	•••	•••		•••	943
	(iii)	Summary	•••		• •					944
8	DISTORTION	<b>v</b>								944
٠.	(i)	Modulation envelo		72						945
	(ii)	Cross modulation	1 TO					(*.*.*):	•••	945
0	55-81152A							•••	49'0 G	945
9.	BIBLIOGRAI	ni	***	11.00		3.55	***	1000000	5579543	
		CHAPTER	24.	OSC	ILL	ATOI	RS			
		O		000			1071-750			
1.	INTRODUCT	ION	***				• • •	*****	***	947
2.	TYPES OF	OSCILLATOR CIRCUI	TS					• (• (• )		949
	(i)	Tuned plate oscil	lator	(12	••	• • •				949
	(ii)	Tuned grid oscilla	ator							950
	(iii)	Hartley oscillator								951
	(iv)	Colpitts oscillator								952
	(v)	Electron-coupled	oscilla	tor .						953
		Negative transcon			illator	rs .			•••	953
3.		B AND C OSCILLAT							•••	954
		OSCILLATOR FREQU					•••		***	955
1000	(i)							***		955
	(ii)	Changes due to s			2				٠	955
	(iii)	Temperature and							****	955
	(iv)	Oscillator harmon								956
5	Charles San	OF FREQUENCY STA						•••		957
		7 <u>2</u>	••			•••	****			958
- 62		A PERMITTANDE OF AND MADE AND				•••		***		959
22.27		USED IN PRACTICAL				•••	•••	•••		959
a.		QUENCY OSCILLATOR								960
10	BIBLIOGRA	STATE STATE IN THE SECOND OF THE SECOND								961
10.	DIBLIOGICE	**** ***	25							
	СНАРТЕР	25. FREQUE	NCY	CONV	ERS	SION	AND	TRA	CKI	1G
1.	THE OPER	ATION OF FREQUEN	CY Co	NVERTE	RS AN	m Mi	XERS		***	962
350	(i)	Introduction						•••		962
	(ii)	General analysis	of ope	ration	comn	non to	all ty	pes		964
	(iii)	The oscillator sec	ction o	of conve	erter	tubes	•••			968
	(iv)	The detailed opera					mixer s	ection	of the	ge.
		converter sta			•••					968
		A STATE OF THE STA								

(xxxii)

OLC1.	ION										PAGE
	(v)	Conclusi		200				222	•••	•••	984
	(vi)	Appendi	x			•••	•••	•••	•••	•••	985
2.	Converter	APPLICA'	TIONS	***			***		•••		987
	(i)	Broadcas	50,000	encies	• • •		•••		•••	•••	987
	(ii)	Short wa			•••	•••		•••	•••		990
	(iii)	Types of			•••	•••	•••				996
3.	SUPERHETER	ODYNE T	RACKING	<b>3</b>			***		•••		1002
	(i)	General			•••		•••	•••	•••	•••	1002
	(ii)	(A)			charts	s for	superhe	terody	ne oscill	ator	
		250	design		•••	***	***	***	9.5.5.1.5.	•••	1005
	71115	(B)	Worked		Contract of the second	•••	•••	***	****		1011
	(iii)	(A)	Padded			ts	***				1013
0520	STATE OF THE STATE	(B)	Worked	exam	ple	•••	***	***			1015
4.	REFERENCES	2****	***	***	**************************************	***	***	***		***	1017
	CHAPTER			AEDI.	ATE	FRE	QUEN	ICY A	AMPL	FIE	RS
1.	CHOICE OF					-3344				•••	1020
	(i)	Reasons							•••	• • •	1020
	(ii)	Common	ily acce	pted in	iterme	diate	frequen	cies	100	•••	1021
2.	Number of	STAGES	***		•••			•••	•••		1021
3.	COMMONLY	used Ci	RCUITS	•••				• • •			1022
	(i)	Mutual	inducta	nce cou	pling						1023
	(ii)	Shunt c	575	200		•••	•••	• • •			1023
	(iii)	Composi	ite i-f t	ransfor	mers	•••	•••				1024
4.	DESIGN ME	ETHODS	•••		•••						1025
	(i)	General			• • •		• • •		•••		1025
	(ii)	Critically	y-couple	d trans	sforme	rs	•••			•••	1026
		(A)	Design	equati	ions an	nd tal	ble	•••	***	***	1026
		( <b>B</b> )	Examp		***	• • •	***		***	•••	1028
		(C)			sion		•••	***	***		1029
		90000000	Conclu		***	*(*)*		•••	•••	•••	1030
	····	(E)					•••	•••	•••	•••	1030
	(iii)	Over-co					•••	•••	•••		1031
			Design	equat	ions ar	nd ta	ble	•••	• • •	***	1031
		(B)		ie	···	•••				***	1033
	(i++)		k meas							6.66	1033
	(iv)	Under-c						unea c	circuits	• • •	1034
		759 333 1000	Single Examp			75 X		•••	• • •		1034
			Under-		d trans				• • •	• • •	1035
			Examp						• • •	•••	1035 1036
S.F.	(v)	F-M i-f				•••	•••	•••	* * *	• • •	1030
	(vi)	I-F tran				•••	***		•	•••	1041
	(vii)	Appendi					 or co-ef	icients	* * *	***	1043
5	VARIABLE S						.g co c	iiczeries		•••	1048
	(i)	General		 rations	•••	•••	13155	0.50		•••	1048
	(ii)	Automat				1.52	23:A38	•••	*050%	•••	1049
6.	25000 CM.00400	BANDWIDT				•••	****	* * *	<b>6.4.4</b> .	•••	
0.	(i)	Behavio				 11t	14.19	•••	***	***	1050
	(ii)	Variable		전에 열심하는 것이 아름이 살아 있다면 하다 되었다.			191819	* * *	•••	****	1050
	(iii)	Design (	<ul> <li>PERSONAL CONTRACTOR OF CONTRACTOR</li> </ul>	The state of the s				filter (	 circuite	•••	1052
	(111)	(A)	Simplif	vino 2	ssiimnt	ione	CI ystai			•••	1053 1053
		(B)	Gain	,,g a					****	200000	1053
		(C)		ariation			dwidth				1054
			Selectiv								1055

				CON	TEN	TS					Dien
SECTI	ON										PAGE
			Crystal c			***	*(*(*)	***	•••		1056
			Position				***		•••	15.55	1057
		(G) (	Other ty	pes of	f crys	tal filter	S	• • • •	3.*S*.*	15151S	1057
	(iv)	Design ex	사용하다 경기가 없는 것이 없는 것이 없다고 없다.						****	ø · · ·	1057
7	DETUNING 1							e-e-e-			1061
1.		Causes of	5								1061
	(i)	Reduction			effect		•••	•••			1062
	(ii)	Reduction	of deti	mmig	CIICCI	.5		• • •			1065
8.	STABILITY	•••		• •		1.00	***	• • •	• • •	1000000	1065
	(i)	Design da	ita .	••	•••	***	***	* * *	•(•)•)	S#1585	
	(ii)	Neutralizir	ig circui	ts	•••		• • •		* * *	•••	1065
9.	DISTORTION						136.				1067
٠.	(i)	Amplitud	[10] [10] [10] [10] [10] [10] [10] [10]		i-f st	ages				#.*.*	1067
	(ii)	Frequenc							•••	•••	1068
	30 150	888	y mouu.								1069
10.	REFERENCES	•••	•••	•••	• • •	• • •		•••	<b></b>	200	
	ALE 1881 1992 - 1138 1488 148 1992			TT ()	T A 3	TD ATT	TOM	ATIC	VOI	TTAAT	F
	CHAPTE	R 27. D	ETEC			ND AU	IOM	AIIC	, 101	CIVI	Ŀ
			12	CO	NTR	OL					
4	A M Down	omone.									1072
1.	A-M DETE	**************************************		•••		***		•0•0•0		70.00	1072
	(i)	Diodes		•••							1072
		`_:	General		• • •		•••	•••		•••	1075
		\/	Diode c			 dota	•••				1075
			Quantita		277.2		•••	• • •	•••		1081
			Miscella			310101	•••	• • •	•••	•••	1082
	(ii)	Other fo				•••	3 <del>737.3</del>	J. 7. 7.	•••	•••	1082
			Grid de			1934.40	10.00	8 <b>*</b> 2**0\$	***	•••	1084
			Power g			on	(*(*(*))		****	•••	
			Plate de			• • •	***	• • •	***	•••	1084
			Reflex of					***		***	1085
		(E)	Regener	rative	detec	tors	• • •	•••	***	***	1086
		(F)	Superre	gener	ative	detectors	s			***	1087
2	F-M DET	137 16		### T							1088
2.		Types o	f detecto	ore in				*****			1088
	(i)	General									1088
	(ii)	Phase di	1000 ACM ACCUSAGE A		***	80.57					1088
	(iii)				∂ <b>•</b> 5•3 <b>€</b>	***	•••		•••		1088
			General		• • •	***	* * *	***		•••	1090
	8	(B)	Design		 _1_		***	•••			1091
	5785 20	(C)	Design		pie		181608	* * *			1095
	(iv)	Ratio de		•••	• • •		***	***		1000	1095
		80.00	Genera		•••		•••		• • •	(***)	1097
		(B)	Operati				•••	• • •			1098
		(C)					•••	•••	* * *		
		(D)	Design			ions	***	•••			1099
		( <b>E</b> )	Practic			***	(*9.808	•••	• • •	•••	1101
		(F)	Measur	remen	t on	ratio det	ectors			•••	1102
3	AUTOMAT	C VOLUME	CONTR	OI.		7. <b>* *</b> * * *					1105
	: [1]	Introdu				***			• • •		1105
	(i) (ii)	Simple							•••		1105
	(ii) (iii)	Delayed						•••			1106
	(iii)	~[시간 맛이 사람이 아니라 이 아이를 하지 않았다.	s of feed	 4	•••	**************************************			***		1109
	(iv)				• • •	\$5\$.40 season				505050 *****	1111
	(v)		circuits		•••	* ************************************	****	57 <b>67464</b>	3000	•••	1111
	(vi)		applicati		• • •	***	•••	•••	2000		1112
	(vii)	100 (2002)	ed a.v.c.	***	2.7.5	***	•••	•••	5 <b>45.454</b>		1113
	(viii)	Audio a		30.00	• • •	• • •	•••	•••	3 <b>3083</b>	***	1114
	(ix)	Modula	tion rise	3640		***	• • •	•••	•••	50 P.0	

(xxxiv)

SEC	CTI	ON									PAGE
		(x)	A.V.C. with batt	ery va	alves	***		***			1114
		(xi)	Special case with	ı simp	le a.v.	c.		***	***		1115
		(xii)	The a.v.c. filter	and it	s time	consta	nts				1115
		335000	A.V.C. character	T. T.		2.4			12.00		1117
			An improved for	rm of	a.v.c.	characte	eristic	·			1118
		020100000000000000000000000000000000000	Design methods	103							1120
1		0.000	.A.V.C.)		•••						1125
4	<b>9</b> %		General operation		***	***	***	15,4077		•••	1125
		(i)	Typical circuits		***	•••	***			* * *	
					 		<b>*</b> (*)*(	• • •	***	•••	1125
_		. 그렇는 이렇게 되었다.	Circuits used wi	in r-r	vi rece	eivers		***	***		1128
5		Noise Limi			3000	***	• • •	<b>***</b>		• • •	1130
6	•	TUNING IN		0.000				10100		7.2.2.	1132
		(i)	Miscellaneous		•••	18.66	•••		•••	•••	1132
		(ii)	Electron Ray tu	경기가 없어 있다면서 되었다.			•••	•••		•••	1133
		(iii)	Null point indic	아이지를 맛있다고 그 때문이다.			Ray	tube		***	1134
		(iv)	Indicators for F	-M re	ceivers		***			***	1135
7		CRYSTAL D	ETECTORS	*0***							1136
		(i)	Old type crystal	detect	tors						1136
		(ii)	Fixed germanium	n crys	tal der	tectors					1136
		(iii)	Fixed silicon cry								1137
		(iv)	Theory of crysta						• • •	•••	1138
		(v)	Transistors								1138
8		REFERENCES					8.8459		5.80.80.95		1138
v	•	TELI ENERGES	55A 5A5	• • •	1,73217	***	#.5.9±	. 500.0	***	•••	1150
			CHAPTER 2	8. R	EFLI	EX AM	MPLI	FIERS			
1		GENERAL D		7641602411							1140
	•	(i)	Description			•••	•••	(5 <b>4.04.0</b> 0)	0.0000		1140
		(ii)	Advantages and			os of re	 flav •		•••	•••	1140
2		2 2	ACTERISTICS OF F						•••	•••	
-	•							EK2	***	***	1142
		(i)	Playthrough (res		voiume	e effect)	***	***		(* * *)	1142
		(ii)	Over-loading	•••		***	***	6.636		•••	1142
		(iii)	Automatic volun				* * *	***			1142
		(iv)	Reduction in per	A 100	ge mo	dulation				•••	1143
		(v)	Negative feedbac		(9 <b>44</b> 43		•••		•••		1143
P. (		(vi)	Operating condi-							•••	1143
3	3.	Design of	PLATE REFLEX S	UPERHI	et. Re	CEIVERS		***			1143
		(i)	General consider	ations							1143
		(ii)	Full a.v.c. appli-	ed to	both s	stages		rex			1143
		(iii)	Fractional a.v.c.			and the second s		***			1143
		(iv)	Full a.v.c. on co				_				1144
4	ł.	DESIGN OF	SCREEN REFLEX								1145
		(i)	Screen reflex red								1145
		(ii)	Comparison bety								1146
5	5.		T.R.F. REFLEX 1	RECEIV	EDC	iid beic		HEALING	111	•••	1146
6			TO REFLEX AMP			DEELEV	Dro		• • •		
•		REFERENCES	TO REFLEX THAT	LIFIER	S AND	NEFLEX	KEC.	EIVEKS	#:#0#01	•••	1146
	C	CHAPTER	29. LIMITE		AND NTRO		MA	TIC F	REQU	EN	CY
1		LIMITERS		200-2002770-0	tota perceptati	eromanak i					1147
85			General	***	• • •	(*.*.*)	•••	*****	***	•••	1147
		(i)	General				• • •	***	\$14.40	•••	1147
-	,	(ii)	Typical circuits					• • •	• • •	•••	1149
4	••		FREQUENCY CON				•••	•••	•••	•••	1150
		(i)	General principl		2.22	•••	•••		***	•••	1150
		(ii)	Discriminators f			• • •	•••	5.55	• • •		1152
		n (iii)	Electronic reacta	nces	•••	•••	•••	***	***	•••	1156
3		REFERENCES						an and	w. w. o. o.		1160

13.22			
C	200		
	BC7	110	ш

PART	5: R	ECTIFICATI	н	$\cup \mathbf{M}$				ERING	A.	ND
		CHAPTE	R 30. J	RECT	IFIC.	ATIO				1161
1. IN	TRODUCT	ON TO RECTIFIC	ATION .			***	• • •			1161
	(i)	Principles of re	ectification	os of s		***	\$15.50 2.50	•••		1164
	(ii)	Rectifier valves	and type	es or si	el vice			THE NAME OF		1165
	(iii)	The use of pu Selenium and	Diisneu C	uide rec	 tifiets			****		1169
	(iv)									1170
2. R		ION WITH COND	ENSER IN	PUT FI						1170
	(i)	Symbols and of Rectification w	ith conde	s neer ir		lter				1170
	(ii)	To determine	neak and	averag	e dio	de cur		\$1 <b>\$</b> 1\$	•••	1174
	(iii)	To determine	ripple pe	rcentag	e	•••				1177
	(iv) (v)	To determine	the trans	former	secon	dary r	.m.s. 0	current		1177
	(vi)	Procedure whe	n comple	ete pub	lished	data	are no	t availab	le	1177
	(vii)	Approximation	s when t	he capa	acitano	ce is la	ırge	***	•••	1180
	(viii)	Peak hot-switc	hing tran	sient p	late ci	urrent		***	•••	1180
	(ix)	The effect of	ripple		• • •	•••	****	98.	• • •	1181
2 D	100 mt (NO 100 m)	TION WITH CHOI	CE INPUT	FILTER	2				•••	1182
J. N	(i)	Rectification w	ith choke	e input	filter					1182
	(ii)	Initial transien	t current			***		•••		1185
4 7	2 2	MER HEATING		Tin.					•••	1185
- FIN 17										1186
5. N		MULTIPLYING R	ECHIFIERS		•••	•••				1186
	(i)	General Voltage double	erc	• • •						118ó
	(ii)	Voltage triples		•••	5.5-01 ***			***		1187
	(iii) (iv)	Voltage diplei			****					1187
	(a)									1188
6. 3	SHUNT D	IODE BIAS SUPPI	1150	***	•••		Serentes			
		CHAPTER	31. FI	LTER	ING	AND	HU	M		
1	INDUCTAN	CE-CAPACITANCE	FILTERS	•••	75.00	***	***		•••	1192
		E-CAPACITANCE				٠			•••	1194
20000 <del>0</del> 0 200		T FILTER NETV								1194
			VORKS	\$0.50	STURASU:				2000	1196
4.	Hum—Gi	Hum due to		 se swith	in the	valves	··· } ···			1196
	(i)	Hum due to	condition	esion a	nd lay	7011t		•••		1198
*	(ii)	Hum due to	n receive	rs and	ampli	fiers		•••		1199
_	(iii)							•••		1200
120		UTRALIZING	10.00	55.5						1201
6.	REFERENC	ES	***	1.535.5	14,537	8.332				
				· TOT	. DO	WED	CLID	DT TEC		
		CHAPTER 32.	VIBR	ATOR	PO	WEK	SUP	LLIES		
	**	o Commun Do	INCIDI ES							1202
1.		GENERAL PR			•••					1202
	(i) (ii)	Operation Vibrator type	 es							1202
	(iii)	Choice of vi			•••			• • •		1203
	(iv)	Coil energizi				7. <b>*. *</b> . *.				
	(v)	Waveform as	nd time	efficienc	<b>cy</b>		***	• • •	• • •	1205
	(vi)		r vibrato	rs for	auto-ra	adio	***	***	. • •	1205

SECT										PAGE
2.	VIBRATOR '	Transformer Des		••			• • •		•••	1205
	(i)	General consider				***		• • •	***	1205
	(ii)	Transformer calc	culations	Fi .	• • •	• • • • • • • • • • • • • • • • • • • •	•••	***		1206
	(iii)	Standards for vi	brator p	ower	transfo	rmers	***			1207
3.	TIMING CA	PACITANCE			***			eroene		1207
E.S.	(i)	The use of the						*:*:		1207
	(ii)	Calculation of ti								1207
	(iii)	Percentage closus								1208
	(iv)	Effect of flux de								1208
1		ON OF VIBRATOR I			-6F		, , , , , ,			
					5×.00	* * *	• • •			1210
5.	12, 24 AND	32 VOLT VIBRAT	OR SUP	PLIES	•••		• • •	• • •	• • •	1211
(	HAPTER	33. CURRE	NT AI	ND V	T IOV	AGE	REG	TIT AT	ГОР	2
20			. 1 111	ND	VOLI	AGE	KEG	ULA	ON	w
1.		REGULATORS	•••		•••	•••	1.1.1	•••		1213
	(i)	Barretters			•••		• • •	***		1213
	(ii)	Negative temper	ature co	efficier	it resis	tors (T	`hermis	tors)	* * *	1214
2.	VOLTAGE F	REGULATORS				***	*1*1*1			1214
	(i)	Gaseous tube vo	ltage re	gulato	rs		•••			1214
	(ii)	Valve voltage re-								1215
3	REFERENCES	. A CONTRACT OF THE PARTY OF TH	<b>2</b> 0-20-10-10-10-10-10-10-10-10-10-10-10-10-10							are as Tre
٠.	TEL BREITOE	t tits man		1907	•••	***	***		* * *	1222
		DIDE (	00115				25 22			
		PART 6: 0	COMP	LETE	REC	EIVE	RS			
	C	HAPTER 34.	TYPE	S OF	A-M	REC	FIVE	25	92	
168					11 111	KLC.				60 × 72 × 128 × 12
1.		ION AND SIMPLE		RS	•••	• • •	•••		***	1223
	(i)	Types of receive	ers .	••	•••	•••	***	****	***	1223
	(ii)					****				1223
	(iii)	Regenerative rec			• • •	• • •				1223
	(iv)	Superheterodyne			***		***			1224
	(v)	Tuned radio-fre	quency	receive	ers					1224
2.	THE SUPER	RHETERODYNE	7.6.6.E				22.2	• • •		1225
3.	THE SYNC	HRODYNE		**		¥42				1226
4.	REFERENCES	s								1227
			•••		•••		• • •	• • •		1221
	CHAPT	ER 35. DESI	GN OI			ETER	ODY	NE A	-M	
			RECE	LIVER	(2)					
1.	INTRODUCT	[전문(전경) - 11222				***				1228
2.	SPECIFICAT	IONS AND REQUIRE	EMENTS .							1229
3.	GENERAL I							204-20		1229
	(i)	A.V.C. and nois	723							1229
	(ii)	Audio-frequency								1234
	(iii)	Hum						######################################		1239
	(iv)	Microphony						\$35050	•••	1241
	(v)	Instability			***	(\$1.5)\$	****	***	• • •	1241
	(vi)	The local oscilla		14.40	• • •	55088	***	***		
	(vii)	Cabinet design		MAN.	54.1 <del>4</del> /47)	(*)*)*	***	• • •	•••	1244
	(viii)	Patings		####\$	•••	• • •		***	• • •	1248
	(ix)	Field testing		• • • • (		4.44		•••	•••	1249
4.	FREQUENCY			• • •		***	•••	•••	•••	1250
	(i)			ivere			•••	•••		1250
	(ii)	Medium frequer Dual wave recei	222 200		Fe (404)	•••	•••	***	•••	1250
	(iii)		52355E5	•••	• • •	•••	•••	5.50	***	1251
	(iv)	Multiband recei	:	• • •	• • •	X****	•••	***	•••	1252
	(14)	Bandspread rece	ivers	•••	•••	****		***		1253

(xxxvii)

SECT	ION									PAGE
5.	A.C. OPERA	ATED RECEIVERS		***	• • •	• • •	•••	•••		1256
	(i)	Four valve rece	ivers	•••	***			•••	***	1256
	(ii)	Five valve recei	vers							1259
	(iii)	Larger receivers	(1) (C)							1260
	(iv)	Communication		rs					.*.	1260
6.	A.C./D.C.	RECEIVERS								1264
::::::::::::::::::::::::::::::::::::::	(i)	Series-resistor o	peration	1						1264
	(ii)	Barretter operati	NA.	•••	105050 1000-0	•••	***			1266
	(iii)	Dial lamps		1905 T		•••	#0#0#0	2.455(7)	•••	1266
	(iv)	Miscellaneous fo					*****		(5)(1)(i	1267
7	NO 60 (CC)	PERATED RECEIVE			•••	•••		STATE S		1268
	. 77	General features				•••	•••			1268
	(i) (ii)	Vibrator-operate				•••	• • •			1270
	(iii)	Characteristics				• • •	(C)	#0.40#5		1272
0	CAR RADIO		n dry t	Jaccorics		•••		***		1275
8.		12.26 3.77.27	 •••••••••••		• • •	•••	•••	200	•••	1275
	(i)	Interference sur		n	***	55.5.5	•••	• • •	•••	1276
	(ii)	Circuit consider		* * # # 6 		7. T.	***	•••	•••	
	(iii)	Valve operating	conditi	ions		•••	37.202	• • •	•••	1277
9.	V	EOUS FEATURES	**************************************	***	• • •	***	***	F. F. (*)		1278
	(i)	Spurious respor		•••			•••	***	***	1278
	(ii)	Reduction of in			•••		* * *	*(*)*)		1279
	(iii)	Contact potenti	al biasir	ng	•••	•••	•••	####		1280
	(iv)	Fuses	•••	• • •	•••	•••	•••	• • • •		1281
	(v)	Tropic proofing			• • •	***	•••	•••	•••	1282
	(vi)	Parasitic oscillat	ions				•••	115	• • •	1283
	(vii)	Printed circuits	***	***			***	***		1283
	(viii)	Other miscellan	eous fe	atures			• • •	*(***)		1285
10.	REFERENCES					***				1285
1.	CI F-M Rece		•••	• • •	F F-λ 	A REC	CEIV	ERS 	1.751):	1287
	(i)	Comparison wit		***	***		***	***		
	(ii)	Aerial and r-f	design							1287
	(iii)								• • •	1287 1287
	7. 3	Local oscillator	design				222		•••	
	(iv)	Local oscillator I-F amplifier	design				2000		•••	1287
	(IV) (V)									1287 1289
2.	(v)	I-F amplifier F-M detection				•••	S0.50		•••	1287 1289 1290
2.	(v) F-M/A-M	I-F amplifier F-M detection RECEIVERS	and A-	 M reje	 ction	•••		•••		1287 1289 1290 1292
2.	(v) F-M/A-M (i)	I-F amplifier F-M detection RECEIVERS R-F section	 and A-	 M reje 	 ction 		••••	•••		1287 1289 1290 1292 1294
2.	(v) F-M/A-M (i) (ii)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier	and A-	 M reje 	ction 	•••			•••	1287 1289 1290 1292 1294 1294
2.	(v) F-M/A-M (i) (ii) (iii)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider	and A-	 M reje 	ction 		***			1287 1289 1290 1292 1294 1294 1294
3.	(v) F-M/A-M (i) (ii) (iii)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider	and A erations	M reje AND	ction AMP	LIFIE		•••		1287 1289 1290 1292 1294 1294 1295 1296
3.	F-M/A-M (i) (ii) (iii) REFERENCES	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider 37. RECEIVERS	and A erations VER	M reje AND	ction AMP	LIFIE	    	ESTS	  	1287 1289 1290 1292 1294 1294 1295 1296
3.	F-M/A-M (i) (ii) (iii) REFERENCES CHAPTER A-M RECE	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider 37. RECEIVERS	and A-	M reje	ction AMP	LIFIE	   R T	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 TD
3.	F-M/A-M (i) (ii) (iii) REFERENCES CHAPTER (i)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider S  37. RECEIVERS Note the section of the section	and A erations VER MEASU	M reje	ction AMP	LIFIE	   	ESTS	   	1287 1289 1290 1292 1294 1294 1294 1295 1296 TD
3.	F-M/A-M (i) (ii) (iii) REFERENCES CHAPTER (i) (ii) (ii)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider  37. RECEIVERS Introduction Definitions	and A erations VER AEASU	M reje	ction AMP	LIFIE	   	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 TD 1297 1297 1297
3.	F-M/A-M (i) (ii) (iii) REFERENCES  CHAPTER  (i) (ii) (ii) (iii) (iii)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider  37. RECEIVERS Introduction Definitions Equipment requipment requipment	and A erations VER AEASU uired	M reje	ction AMP	LIFIE	 R T	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 1297 1297 1297 1297 1297
3.	F-M/A-M (i) (ii) (iii) REFERENCES  A-M RECE (i) (ii) (iii) (iii) (iii) (iv)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider  37. RECEIVERS Note the section of th	and A erations VER AEASU uired	M reje	ction AMP	LIFIE	   	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 TD 1297 1297 1297 1297 1298 1300
3.	F-M/A-M (i) (ii) (iii) REFERENCES  A-M RECE (i) (ii) (iii) (iii) (iv) (iv) (v)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider S  37. RECEIVERS Introduction Definitions Equipment requirements Measurements Measurements Measurements	and A erations VER AEASU uired	M reje	ction AMP	LIFIE	 R T	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 1297 1297 1297 1297 1297 1297 1298 1300 1301
3.	F-M/A-M (i) (ii) (iii) REFERENCES  A-M RECE (i) (ii) (iii) (iii) (iv) (iv) (v) (vi)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider S  37. RECEIVERS Introduction Definitions Equipment requipment requipment requipments Measurements Measurements Measurements Tests	and A erations VER AEASU uired	M reje	AMP AMP ENTS	LIFIE	   	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 1297 1297 1297 1297 1297 1297 1297 1297
3.	F-M/A-M (i) (ii) (iii) REFERENCES  CHAPTER  (i) (ii) (ii) (iii) (iv) (iv) (v) (vi) F-M RECE	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider S  37. RECEIVERS Introduction Definitions Equipment requipment requipments Measurements Measurements Tests IVERS	and A erations VER AEASU uired and ope	M reje	ction AMP ENTS conditi	LIFIE	 R T	ESTS	   	1287 1289 1290 1292 1294 1294 1294 1295 1296 1297 1297 1297 1297 1297 1297 1297 1298 1300 1301 1302 1314
3.	F-M/A-M (i) (ii) (iii) REFERENCES  A-M RECE (i) (ii) (iii) (iii) (iv) (iv) (v) (vi)	I-F amplifier F-M detection RECEIVERS R-F section I-F amplifier General consider S  37. RECEIVERS Introduction Definitions Equipment requipment requipment requipments Measurements Measurements Measurements Tests	and A erations VER AEASU uired and ope	M reje	AMP AMP ENTS	LIFIE	   	ESTS	   	1287 1289 1290 1292 1294 1294 1295 1296 1297 1297 1297 1297 1297 1297 1297 1297

(xxxviii)

SECT					PAGE
	(iii)	Test procedures and operating conditions	202		1315
	(iv)	Receiver adjustments			1316
	(v)	Performance tests			1317
3.	Audio Fre	QUENCY AMPLIFIERS			1321
	(i)	Equipment and measurements			1321
	(ii)	Tests			1321
1					1325
4.				• • •	
	(i)	Measurement of coefficient of coupling			1325
	(11)	Measurement of primary resonant frequencies of aer	hai and r	-I	
	N 4 2 4 2 1	coils		• • •	1325
	(iii)	Measurement of distributed capacitance across co	oils	• • •	1325
5.	REFERENCES		***	• • •	1327
		PART 7: SUNDRY DATA			
	CHAPTI	ER 38. TABLES, CHARTS AND SUNDE	DV DA	ТΔ	
	CHAPII	2K 36. IABLES, CHARIS AND SUNDI	CI DA	1 A	
1.	Units				1329
	(i)	General physical units			1329
	(ii)	Electrical and magnetic units			1331
	(iii)	Dhatamatuia unita			1334
	30			•••	1334
_	(iv)	Temperature			
2.	COLOUR CO				1335
	(1)	Colour code for fixed composition resistors	• • •	• • •	1335
	(ii)	Colour code for fixed wire wound resistors		•	1336
	(iii)	Table of R.M.A. colour code markings for resis	tors		1337
	(iv)	Colour code for moulded mica capacitors			1340
	(v)	Colour code for ceramic dielectric capacitors			1341
	(vi)	Colour code for i-f transformers			1342
	(vii)	Colour code for a-f transformers and output tran	nsformer	s	1342
	(viii)	Colour code for power transformers			1342
	(ix)	C-1			1343
	0.27.53	Colour and for change wining		•••	1343
	(x)	Salting States and Article March 18 Control 2001 (States and States and States and States and States and States	<b>***</b> ***	* * *	
	(xi)	Colour code for battery cables	(#.#5#)	• • •	1344
	(X11)	Colour code for metallized paper capacitors	* * *	• • •	1344
3.		RESISTORS AND CAPACITORS	•••	• • •	1344
	(i)	Standard fixed composition resistors			1344
	(ii)	Standard fixed wire wound resistors			1346
	(iii)	Fixed paper dielectric capacitors in tubular non-me	etallic cas	ses	1347
	(iv)	Metal encased fixed paper dielectric capacitors for	d.c. app	li-	
		cation	***		1349
	(v)	Standard fixed mica dielectric capacitors		•••	1351
	(vi)	Crandard coromia dialectria comocitore			1352
		^ 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
	(vii)	National Control of the Control of t		• • •	1354
	(viii)	Standard variable composition resistors	•••	• • •	1356
	(ix)	Standard metallized paper dielectric capacitors	•••	• • •	1357
	(x)	Standard electrolytic capacitors	•••	•••	1357
	(xi)	References to standard resistors and capacitors			1358
4.	STANDARD	Frequencies			1361
	(i)	Standard frequency ranges			1361
	(ii)	Frequency bands for broadcasting			1361
	(iii)	Standard intermediate frequencies			1361
5	000 BB (400	Table			1362
٥.	· · · ·	W/ 1 al Common common table		•••	
	(1)	. 그렇게 잘 맞게 하고 교계에 없는 ^ 나라 ^ 어린 이 아이에 어린 이 살아 보고 있는데 이 살아 있다. 그 가게 되었다면 하는데 그 그렇게 하는데 그 그렇게 하는데 그 그렇게 하는데 그 그 때문에 살아 먹는데 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	• • •	***	1362
•	(ii)	Wavelengths of electromagnetic radiations	•••	* * *	1363
6.		SYMBOLS AND ABBREVIATIONS	* * *	• • •	1363
	(i)	Introduction	***		1363
	(ii)	Multipliers		***	1363

SECTI					PAGE
	(iii)	Come and and			1363
	(iv)	Transportation of the state of		• • •	1364
	(v)	Successipis in any and any and any	• • •		1364
	(vi)	B		• • •	1365 1366
	(vii)		•••		1366
	(viii)	- 1000000000000000000000000000000000000	•••	••••	1367
	(ix)	of the contract of the contrac	5-5-3).	•••	1369
	(x)	References to periodicals References to standard symbols and abbreviations	•••	***	1369
_	(xi)		• • •	••••	
7.			•••	•••	1370
8.		OF MATERIALS AND CHEMICAL AND PHYSICAL CONSTA	ANTS	•••	1372
	(i)		• • •	•••	1372
	(ii)	and the first that the first the first that the first th	•••	•••	1374
	(iii)		•••	***	1375
	(iv)		•••	***	1375
	(v)	Resistance of a conductor at any temperature		•••	1376
	(vi)	References to properties of materials		• • •	1376 1376
	(vii)	Chemical and physical constants		• • •	
9.		IMPEDANCE AND RESONANCE		• • •	1377
	(i)	Inductive reactances	• • •	• • •	1377
	(ii)	Capacitive reactances	•••	• • •	1378
	(iii)			• • •	1380
	(iv)	Impedance of reactance and resistance in series	* * *	•••	1382
	(v)	Resonance			1386
	(vi)	Approximations in the calculation of impedance for	reacta	nce	1206
	-X	and resistance in series and parallel			1386
2002	(vii)	Reactance chart	* * *	•••	1387
10.					1388
	(i)	Standard American screws used in radio manufact	ture	•••	1388 1389
	(ii)	B.A. screw threads	1.50.50		1389
	(iii)	Whitworth screw threads	5838		1390
	(iv)	Unified screw threads Drill sizes for self-tapping screws	*:*(*)	3.00	1391
	(v)	TV7 1	*)* *:		1391
	(vi) (vii)	TO 1 . 1 111 1-	F ( )		1392
	(vii)	Sheet steel gauges			1393
	111 ( 2010) 2010	And the state of t			1394
11.	I EMPERATU	RE RISE AND RATINGS		* * *	
12.	Fuses				1395
13.	CHARACTER	ISTICS OF LIGHT; PANEL LAMPS		***	1396
	(i)	Visibility curves of the human eye and relative spect	ral ene	rgy	
		curves of sunlight and tungsten lamp			1396
	(ii)	Velocity of light			1396
	(iii)	American panel lamp characteristics			1397
14.	GREEK ALI	PHABET			1397
15.	DEFINITION	ıs			1398
16	DECIMAL F	QUIVALENTS OF FRACTIONS		***	1404
17.		AND SUD-MILLTIDLES			1405
115190	655		*****	505/52	1406
18.		Numerical values		•••	1407
10	(ii) Wire Tabi	Factorials	***	*(************************************	1408
			***		
	Logarithn		250 X 25	***	1418
21.		ETRICAL TABLES	•••	• • •	1420
		sines, cosines and tangents	•••	• • •	1421
22	LOG SCATI	S AND LOG SCALE INTERPOLATOR			1422