

VALVE ELECTRONIC **CV1605**

GENERAL POST OFFICE: E-IN-C (W)

(POVT 60)

Specification: G.P.O./CV 1605/Issue 2 Dated: November, 1956 To be read in conjunction with K 1001	<u>SECURITY</u>	
	<u>Specification</u> Unclassified	<u>Valve</u> Unclassified

—————> indicates a change

<u>TYPE OF VALVE:</u> Triode, water-cooled <u>CATHODE:</u> Directly heated tungsten filament <u>ENVELOPE:</u> Metal-glass <u>PROTOTYPE</u> 4013 C		<u>MARKING</u> See K 1001/4 Additional markings required (See notes A. B.&C.) Serial No..... Filament Volts.....	
<u>RATING</u>		Note	<u>BASE</u> None
Filament voltage (V)	As marked	B	<u>CONNECTIONS</u> See drawing on page 4
Nominal filament current (A)	36.0	D	
Max. anode voltage (kV)	6.0	D	
Max. anode current (A)	0.7	D	
Max. anode dissipation (kW)	5.0	E	
Max. operating frequency (Mc/s)	22	E	
Amplification factor	20.0		
Anode impedance (ohms)	5700		
Max. anode voltage at 22 Mc/s (kV)	5.0		
Min. rate of water flow (gals/min)	3.0		
<u>CAPACITANCES (pF)</u>			<u>DIMENSIONS</u> See drawing on page 4
C _{ag} (nominal)	18.0		<u>PACKING</u> See K 1001/7.3
C _{ac} (nominal)	2.0		
C _{ge} (nominal)	14.0		
<u>NOTES</u>			
A. The serial numbers will be allotted by the Inspecting Officer.			
B. The Marked Voltage is defined on page 2, test (a).			
C. It is not essential that the additional markings shall appear within the frame.			
D. The maximum frequency of operation for these ratings is 15 Mc/s.			
E. Measured with I _a = 0.8 A, and E _g = -50V (A.C. filament) or -43V (D.C. Filament).			

TESTS

The tests shown in Table I, or, alternatively those shown in Table II, shall be performed in addition to those applicable in K 1001.

TABLE I (for A.C. filament heating).

	TEST CONDITIONS				TEST	LIMITS		No. Tested	Note
	Vf (AC)	Va (kV)	Vg (V)	Ia (A)		Min.	Max.		
(a)	Read	3	3000	-	Vf. Minimum required for peak emission of 3 amps. To be known as "Marked Voltage" (V)	13.5	14.5	100%	1
(b)	MV	0	0	-	If (A)	34.5	37.5	100%	
(c)	MV	10	Adjust	0.8	Reverse Ig (μA)	-	55.0	100%	2
(d)	MV	5	0	Read	Ia (A)	0.65	0.85	100%	
(e)	MV	Read	0	0.8	μ	18.6	21.6	100%	
		Read	- 100						
(f)	MV	7.5	-	-	Oscillation efficiency (%)	60	-	100%	3
(g)	MV	10	Adjust	0.8	Reverse Ig (μA)	-	55.0	100%	2

TABLE II (for D.C. filament heating).


	TEST CONDITIONS				TEST	LIMITS		No. Tested	Note
	Vf (DC)	Va (kV)	Vg (V)	Ia (A)		Min.	Max.		
(a)	Read	3	3000	-	Vf. Minimum required for peak emission of 3 amps. To be known as "Marked Voltage" (V)	13.5	14.5	100%	1
(b)	MV	0	0	-	If (A)	34.5	37.5	100%	
(c)	MV	10	Adjust	0.8	Reverse Ig (μA)	-	55.0	100%	2
(d)	MV	5	7	Read	Ia (A)	0.65	0.85	100%	
(e)	MV	Read	7	0.8	μ	18.6	21.6	100%	
		Read	- 93						
(f)	MV	7.5	-	-	Oscillation efficiency (%)	60	-	100%	3
(g)	MV	10	Adjust	0.8	Reverse Ig (μA)	-	55.0	100%	2

NOTES

1. The test shall be made in accordance with K 1001/A V.
2. The duration of tests (c) and (g) shall be 15 minutes each, and the reverse grid current shall not be rising at the end of either test. Test (c) shall precede test (f), and test (g) shall follow immediately upon the end of test (f).
3. The duration of test (f) shall be 15 minutes, and the anode current shall not be less than 1.1 A.
The test shall be made by causing the valve to oscillate in an approved circuit, the oscillation frequency being not less than 15 Mc/s. In the event of such a circuit not being available for this test, the valve may be tested in an oscillatory circuit of a frequency not less than 800 kc/s, but, if this applies, the right is reserved to conduct test (f) on service premises in a circuit of frequency not greater than 15 Mc/s, and to reject any valve found to be unsatisfactory at this higher frequency during the test.

CV1605

OUTLINE DRAWING



CV1605/2/4

Z.13013.R.