

12SA7

Pentagrid Converter

The 12SA7 is the same as the 6SA7 except for the following items:

Heater Characteristics and Ratings:

Voltage (AC or DC)	12.6 volts
Current	0.150 amp

12SJ7

Sharp-Cutoff Pentode

The 12SJ7 is the same as the 6SJ7 except for the following items:

Heater Characteristics and Ratings:

Voltage (AC or DC)	12.6 volts
Current	0.150 amp

12SL7GT

High-Mu Twin Triode

The 12SL7GT is the same as the 6SL7GT except for the following items:

Heater Characteristics and Ratings:

Voltage (AC or DC)	12.6 volts
Current	0.150 amp

12SN7GTA

Medium-Mu Twin Triode

The 12SN7GTA is the same as the 6SN7GTA except for the following items:

Heater Characteristics and Ratings:

Voltage (AC or DC)	12.6 volts
Current	0.300 amp



12SQ7

Twin Diode-Medium-Mu Triode

The 12SQ7 is the same as the 6SQ7 except for the following items:

Heater Characteristics and Ratings:

Voltage (AC or DC)	12.6	volts
Current	0.150	amp

12V6GT

Beam Power Tube

The 12V6GT is the same as the 6V6GT except for the following items:

Heater Characteristics and Ratings:

Voltage (AC or DC)	12.6	volts
Current	0.225	amp

12W6GT

Beam Power Tube

The 12W6GT is the same as the 6W6GT except for the following items:

Heater Characteristics and Ratings:

Current	0.600	amp
Voltage (AC or DC)	12.6	volts
Warm-up time (Average)	11	sec

Peak Heater-Cathode Voltage:

Heater negative with respect to cathode. . . .	300 max.	volts
Heater positive with respect to cathode. . . .	200 ^a max.	volts

^a The dc component must not exceed 100 volts.

