



6678

6678/6U8-A

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*For use in mobile communications equipment***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathodes:

Voltage. 6.3 ± 20%* ac or dc volts

Current at 6.3 volts 0.45 amp

Direct Interelectrode Capacitances:

	<i>Without External Shield</i>	<i>With External Shield^o</i>	
<i>Triode Unit:</i>			
Grid to plate.	1.8	1.8	μμf
Grid to cathode and heater	2.5	2.5	μμf
Plate to cathode and heater	0.4	1	μμf
<i>Pentode Unit:</i>			
Grid No.1 to plate	0.01 max.	0.006 max.	μμf
Grid No.1 to cathode & grid No.3 & internal shield, grid No.2, and heater	5	5	μμf
Plate to cathode & grid No.3 & internal shield, grid No.2, and heater. .	2.6	3.5	μμf
Heater to cathode (Each unit).	3	3 ^o	μμf

Characteristics, Class A₁ Amplifier:*With heater voltage of 6.3 volts*

	<i>Triode Unit</i>	<i>Pentode Unit</i>	
Plate Supply Voltage.	150	250	volts
Grid-No.2 (Screen-grid) Supply Voltage.	—	110	volts
Cathode Resistor.	56	68	ohms
Amplification Factor.	40	—	
Plate Resistance (Approx.). .	5000	400000	ohms
Transconductance.	8500	5200	μmhos
Plate Current	18	10	ma
Grid-No.2 Current	—	3.5	ma
Grid-No.1 Voltage (Approx.) for plate $\mu a = 10$	-12	-10	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-3/16"
Maximum Seated Length	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip). .	1-9/16" ± 3/32"
Diameter.	0.750" to 0.875"

6678



6678/6U8-A

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

Dimensional Outline. See General Section
 Bulb T6-1/2
 Base Small-Button Noval 9-Pin (JEDEC No. E9-1)
 Basing Designation for BOTTOM VIEW -9AE

Pin 1—Triode Plate
 Pin 2—Pentode
 Grid No. 1
 Pin 3—Pentode
 Grid No. 2
 Pin 4—Heater
 Pin 5—Heater
 Pin 6—Pentode Plate



Pin 7—Pentode
 Cathode,
 Pentode
 Grid No. 3,
 Internal
 Shield
 Pin 8—Triode Cathode
 Pin 9—Triode Grid

CONVERTER SERVICE

Maximum Ratings, Design-Maximum Values:

	Triode Unit as Osc.	Pentode Unit as Mixer	
PLATE VOLTAGE.	330 max.	330 max.	volts
GRID-No. 2 (SCREEN-GRID) SUPPLY VOLTAGE	—	330 max.	volts
GRID-No. 2 VOLTAGE.	—	See Grid-No. 2 Input	
<i>Rating Chart at front of Receiving Tube Section</i>			
GRID-No. 1 (CONTROL-GRID) VOLTAGE:			
Positive-bias value.	0 max.	0 max.	volts
GRID-No. 2 INPUT:			
For grid-No. 2 voltages up to 165 volts	—	0.55 max.	watt
For grid-No. 2 voltages be- tween 165 and 330 volts.	—	See Grid-No. 2 Input	
<i>Rating Chart at front of Receiving Tube Section</i>			
PLATE DISSIPATION.	3 max.	3 max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200 max.	200 max.	volts
Heater positive with respect to cathode	200 [▲] max.	200 [▲] max.	volts

* When the heater is operated from storage-battery-with-charger supply or similar supplies, the normal battery-voltage fluctuation may be as much as 35 per cent or more. Although such variation in heater voltage is permissible for short periods, reliability can be increased with improved supply-voltage regulation.

^o With external shield JEDEC No. 316 connected to cathode of unit under test except as noted.

[●] With external shield JEDEC No. 315 connected to ground.

[▲] The dc component must not exceed 100 volts.



6678/6U8-A

6678

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling Life Performance:

This test is performed on a sample lot of tubes from each production run. A minimum of 2000 cycles of intermittent operation is applied under the following conditions: heater volts = 7.5 cycled one minute on and one minute off, heater 135 volts positive with respect to cathode, and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Transconductance at Reduced Heater Voltage:

Triode Unit:

Average value. 6800 μ hos
With heater volts = 5, plate supply volts = 150, and cathode resistor (ohms) bypassed = 56.

Pentode Unit:

Average value. 4100 μ hos
With heater volts = 5, plate supply volts = 250, grid-No. 2 supply volts = 110, and cathode resistor (ohms) bypassed = 68.