

TUNG-SOL

CATHODE RAY

THE 17CP4 AND 17CP4A ARE DIRECT VIEW PICTURE TUBES DESIGNED FOR USE IN TELEVISION APPLICATIONS. THEY ARE IDENTICAL WITH THE FOLLOWING *EXCEPTION*:

17CP4 - *PROSTED FACEPLATE*17CP4A - *UNPROSTED FACEPLATE*

THEIR COMMON FEATURES INCLUDE:

UNIPOTENTIAL CATHODE	FILTER GLASS FACEPLATE
14 5/8" X 11" RASTER SIZE	MAGNETIC FOCUS & DEFLECTION
RECTANGULAR METAL CONSTRUCTION	EXTERNAL SINGLE FIELD ION TRAP

ELECTRICAL DATA

FOCUSING METHOD		MAGNETIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.)		
HORIZONTAL	66	DEGREES
VERTICAL	50	DEGREES
DIAGONAL	70	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.)		
CATHODE TO ALL OTHER ELECTRODES	5	μf
GRID #1 TO ALL OTHER ELECTRODES	6	μf

OPTICAL DATA


PHOSPHOR NUMBER	SULFIDE TYPE	NO. 4
FLUORESCENT COLOR		WHITE
PHOSPHORESCENT COLOR		WHITE
PERSISTENCE		MEDIUM
FACEPLATE LIGHT TRANSMISSION AT CENTER (APPROX.)	65	PERCENT

MECHANICAL DATA

OVERALL LENGTH	19	INCHES
GREATEST DIMENSIONS OF BULB		
DIAGONAL	16 13/16 \pm 3/16	INCHES
WIDTH	15 15/16 \pm 1/8	INCHES
HEIGHT	12 1/4 \pm 1/8	INCHES
MINIMUM USEFUL SCREEN DIMENSIONS		
WIDTH	14 5/8	INCHES
HEIGHT	11	INCHES
BULB CONTACT	METAL SHELL LIP	
BASE	SMALL SHELL DUODECAL 5 PIN	B5-57
BASING		12D
BASE ALIGNMENT		
PIN #6 ALIGNS WITH HORIZONTAL PICTURE AXIS \pm 10 DEGREES		

PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID NO. 1
 PIN 10 - GRID NO. 2
 PIN 11 - CATHODE



PIN 12 - HEATER
 METAL SHELL LIP:
 ANODE

BOTTOM VIEW

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS
DESIGN CENTER VALUES

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC ANODE VOLTAGE ^A	16 000	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	410	VOLTS
MAXIMUM GRID #1 VOLTAGE		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	180	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	180	VOLTS

^A THE PRODUCT OF ANODE VOLTAGE AND AVERAGE ANODE CURRENT SHOULD BE LIMITED TO 6 WATTS.

TYPICAL OPERATING CONDITIONS ANDECHARACTERISTICS

DC ANODE VOLTAGE ^B	12 000	VOLTS
DC GRID #2 VOLTAGE	300	VOLTS
DC GRID #1 VOLTAGE ^C	-33 TO -77	VOLTS
DC FOCUSING COIL CURRENT ^D (APPROX.)	96 ± 6%	MA.
DC ION TRAP CURRENT STANDARD COIL #111 (APPROX.)	70	MA.
FIELD STRENGTH OF ION TRAP MAGNET	45	GAUSSES

^B BRILLIANCE AND DEFINITION DECREASE WITH DECREASING VOLTAGE. IN GENERAL, THE ANODE VOLTAGE SHOULD NOT BE LESS THAN 12,000 VOLTS.

^C VISUAL EXTINCTION OF UNDEFLECTED FOCUSED SPOT.

^D FOR STANDARD FOCUS COIL #109, OR EQUIVALENT, WITH THE COMBINED GRID #1 BIAS VOLTAGE AND VIDEO SIGNAL VOLTAGE ADJUSTED TO PRODUCE A HIGHLIGHT BRIGHTNESS OF 30 FOOT LAMBERTS ON A 10 11/16" BY 14 3/8" PICTURE SIZE. DISTANCE FROM REFERENCE LINE TO CENTER OF AIR GAP ON FOCUS COIL SHALL BE 3.0 INCHES.

CIRCUIT VALUES

MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEGOHMS
------------------------------------	-----	---------

TUNG-SOL

