

# EDISWAN

## ESU104

### HALF-WAVE XENON RECTIFIER

### TENTATIVE

---

#### GENERAL

The ESU104 is a directly heated half-wave Xenon Rectifier requiring a heating delay time of 10 seconds. Two rectifiers in a Full Wave circuit will give an output of 0.5 amps at 3.2kV or 1.0 amp at 1.6kV. This rectifier may be operated in the ambient temperature range—50°C to +75°C.

#### RATING

Filament Voltage (volts)	$V_f$	4.0	
Filament Current (amps)	$I_f$	2.8	
Maximum Peak Inverse Voltage (kV)	PIV(max)	5.0	10.0
Maximum Peak Anode Current (amps)	$I_a(pk)max$	2.0	1.0
Maximum Mean Anode Current (amps)	$I_a(av)max$	0.5	0.25
Maximum Voltage Drop (volts)			12.0
Minimum Heating Time (secs)			10
Ambient Temperature Range (°C)			—50 to +75

#### DIMENSIONS

Maximum Overall Length	(mm)	160
Maximum Seated Height	(mm)	144
Maximum Diameter	(mm)	52
Approximate Nett Weight	(ozs)	4
Approximate Packed Weight	(ozs)	8

#### MOUNTING POSITION—Unrestricted

#### TYPICAL OPERATION—Full Wave (2 valves)

Peak Inverse Voltage Rating (kV)	PIV(max)	5.0	10.0
Output Voltage (kV)	$V_{out}$	1.6	3.2
Output Current (amps)	$I_{out}$	1.0	0.5


ESU104

**EDISWAN**  
**ESU104**  
**HALF-WAVE XENON RECTIFIER**  
**TENTATIVE**

---

TOP CAP—CT3

BASE—B4



Viewed from free end of pins

VALVE HOLDER—Ediswan Clix VH300/4, VH42/4

TOP CAP CONNECTOR—Ediswan Clix TC433

CONNECTIONS

Pin 1	No Connection	NC
Pin 2	No Connection	NC
Pin 3	Filament	f
Pin 4	Filament, Shield	f,s
Top Cap	Anode	a